

ANYTOUR X E+ 3

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2, 75Nm, PedalPlus 6-sensor technology
CONTROLLER	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERY	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, L, XL
COLORS	Pyrite Brown / Black, Snow Drift / Black
FRAME	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27.5" Frame-set, KSA40 Kickstand
FORK	SR Suntour XCR32 ATB LO 27.5" Coil 100mm
SHOCK	n/a
COMPONENTS	
HANDLEBAR	Giant Contour Comfort Riser 31.8x690mm
GRIPS	Giant Comfort Ergo Microtech Plus Lock-on
STEM	Giant Contour, EVO integrated, high adjustable
SEATPOST	Suspension 2-bolt micro-adjustable, 30,9x270mm
SADDLE	Selle Royal Vivo Ergo Unisex
PEDALS	VP VPES37, PP platform / Anti-slip
DRIVETRAIN	
SHIFTERS	Shimano Deore 10-speed
FRONT DERAILLEUR	n/a
REAR DERAILLEUR	Shimano Deore, 10-speed, Shadow+
BRAKES	Shimano BR-MT200, hydraulic disc, 180mm
BRAKE LEVERS	Shimano BL-MT200
CASSETTE	Shimano Deore, CS-M4100, 11-46T, 10-speed
CHAIN	KMC e.10 Sport, e-bike optimized
CRANKSET	Alluminum 42T
BOTTOM BRACKET	n/a

WHEELS	
RIMS	Giant eX25, Tubeless Ready, 584x25 Aluminium
HUBS	Shimano HB-MT200 100x9mm QR Disc [F] Shimano FH-QC400-HM [R]
SPOKES	Stainless
TIRES	Schwalbe Smart Sam Plus 57-584 (27.5 x 2.25"), DD, GreenGuard, ADDIX, E-50
EXTRAS	KSA40 direct mount kickstand
ACCESSORIES	
LIGHTING	Giant Recon HL50, 50 lux [F]AXA Juno 6-12V E-bike tail light [R]
LOCK	ABUS Xplus Battery Lock / Abus 5755L XPlus NR
CARRIER	MIK HD rack. System bag & basket compatible

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	340	410	480	550
Seat Tube Angle	74,0°	73,0°	72,0°	72,0°
Top Tube Length (mm)	570	590	610	630
Head Tube Length (mm)	130	130	170	170
Head Tube Angle	69,5°	69,5°	69,5°	69,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	87	87	87	87
Wheelbase (mm)	1120	1128	1138	1158
Chain Stay Length (mm)	470	470	470	470
Bottom Bracket Drop (mm)	50	50	50	50
Stack (mm)	625	625	662	662
Reach (mm)	391	399	395	415
Stand Over Height (mm)	592	564	524	488
Handlebar Width (mm)	690	690	690	690
Stem Length (mm)	90	90	110	110
Crank Length (mm)	170	170	170	170
Wheel Size	27.5"	27.5"	27.5"	27.5"

All specifications listed are subject to change without notice.