

ANYTOUR X E+ 3



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	Giant SyncDrive Sport2, 75Nm, PedalPlus 6-sensor technology
OHJAUSYKSIKKÖ	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
NÄYTTÖ	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
AKKU	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
LATURI	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
YHTEYDET MUIHIN LAITTEISIIN	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RUNKO	
KOOT	S, M, L, XL
VÄRIT	Pyrite Brown / Black, Snow Drift / Black
RUNKO	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27,5" Frame-set, KSA40 Kickstand
HAARUKKA	SR Suntour XCR32 ATB LO 27.5" Coil 100mm
ISKUNVAIMENNIN	n/a
KOMONENTIT	
OHJAUSTANKO	Giant Contour Comfort Riser 31.8x690mm
GRIPIT	Giant Comfort Ergo Microtech Plus Lock-on
OHJAINKANNATIN	Giant Contour, EVO integrated, high adjustable
SATULATOLPPA	Suspension 2-bolt micro-adjustable, 30,9x270mm
SATULA	Selle Royal Vivo Ergo Unisex
POLKIMET	VP VP537, PP platform / Anti-slip
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Deore 10-speed
ETUVAIHTAJA	n/a
TAKAVAIHTAJA	Shimano Deore, 10-speed, Shadow+
JARRUT	Shimano BR-MT200, hydraulic disc, 180mm
JARRUKAHVAT	Shimano BL-MT200
RATASPAKKA	Shimano Deore, CS-M4100, 11-46T, 10-speed
KETJUT	KMC e.10 Sport, e-bike optimized
KAMPISARJA	Alluminum 42T
KESKIÖ	n/a

RENKAAT	
VANTEET	Giant eX25, Tubeless Ready, 584x25 Aluminium
NAVAT	Shimano HB-MT200 100x9mm QR Disc [F] Shimano FH-QC400-HM [R]
PINNAT	Stainless
RENKAAT	Schwalbe Smart Sam Plus 57-584 (27.5 x 2.25"), DD, GreenGuard, ADDIX, E-50
LISÄTIEDOT	KSA40 direct mount kickstand
TARVIKKEET	
VALOT	Giant Recon HL50, 50 lux [F]AXA Juno 6-12V E-bike tail light [R]
LUKKO	ABUS Xplus Battery Lock / Abus 5755L XPlus NR
TAVARATELINE	MIK HD rack. System bag & basket compatible

Suositusinta: 3 939,00 €

GEOMETRIA

RUNKO	S	M	L	XL
Satulaputken pituus (mm)	340	410	480	550
Satulaputken kulma	74,0°	73,0°	72,0°	72,0°
Vaakaputken pituus (mm)	570	590	610	630
Emäputken pituus (mm)	130	130	170	170
Emäputken kulma	69,5°	69,5°	69,5°	69,5°
Haarukan offset (mm)	44	44	44	44
Trail-mitta (mm)	87	87	87	87
Akseliväli (mm)	1120	1128	1138	1158
Takahaarukan alaputken pituus (mm)	470	470	470	470
Keskiön pudotus (mm)	50	50	50	50
Stack-mitta (mm)	625	625	662	662
Reach-mitta (mm)	391	399	395	415
Standover-mitta (mm)	592	564	524	488
Ohjaustangon leveys (mm)	690	690	690	690
Ohjainkannattimen pituus (mm)	90	90	110	110
Kammen pituus (mm)	170	170	170	170
Rengaskoko	27.5"	27.5"	27.5"	27.5"

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.