

ANYTOUR X E+ 3

GIANT



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology
TIPALO	Single sided RideControl Ergo 4 w/ RideControl Go2 turn-on button
PRIKAZOVALNIK	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATERIJA	Giant EnergyPak 625Wh
CHARGER	Giant EnergyPak 4A smart charger
OKVIR	
VELIKOSTI	S, M, L, XL
OKVIR	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27,5" Frame-set, KSA40 Kickstand
VILICE	SR Suntour MOBIE 34 2CR Air 100mm travel, 15x100mm thru-axle
KOMPONENTE	
KRMILO	Giant Contour Comfort Riser 31.8x690mm
GRIPS	Giant Comfort Ergo Microtech Plus Lock-on
OPORA KRMILA	Giant Contour, EVO integrated, high adjustable
OPORA SEDEŽA	Suspension dropper post, 30.9mm
SEDEŽ	Selle Royal Vivo Ergo Unisex
PEDALA	Large platform pedal, 28-pins, PP cage, Steel axle
POGON	
PRESTAVNE ROČICE	Shimano Cues LinkGlide
ZADNJI MENJALNIK	Shimano Cues LinkGlide, 10-speed, Shadow+
ZAVORE	Shimano MT-200, hydraulic disc, 180mm [F/R]
ZAVORNE ROČICE	Shimano MT-200
VERIŽNIK	Shimano Cues LinkGlide, 10-speed, 11-43T
VERIGA	Shimano LinkGlide
GONILKE Z VERIŽNIKI	42T, Forged aluminum crank arms

OBROČNIKI	
OBROČI	Giant eX25 27.5 Tubeless Ready Aluminium 584x25
PESTA	Shimano 15x100mm [F] Shimano FH-QC400-HM [R]
NAPERE	stainless
PLAŠČI	Schwalbe Smart Sam Plus, 584x57C (27.5 x 2.25"), DD, GreenGuard, Addix, E-50
DODATKI	KSA40 direct mount kickstand
DODATNA OPREMA	
SVETILA	Giant Recon HL50, 50 lux [F] Aegis carrier integrated tail light[R]
KLJUČAVNICA	ABUS Xplus Battery Lock / Abus 6950L XPlus NR
PRTLJAŽNIK	MIK HD rack. System bag, basket and Aegis radar compatible
BLATNIKI/ŠČITNIK VERIGE	Aluminium Fender w/ Z-Reflector, Pistol shape

GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	340	410	480	550
Kot sedežne cevi	74,0°	73,0°	72,0°	72,0°
Top Tube Length (mm)	570	590	610	630
Višina glave okvirja (mm)	130	130	170	170
Krmlilni kot	69,5°	69,5°	69,5°	69,5°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	85,4	85,4	85,4	85,4
Medosna razdalja (mm)	1120,1	1128,3	1138,1	1158,1
Dolžina cevi ob verigi (mm)	470	470	470	470
Bottom Bracket Drop (mm)	50	50	50	50
Oddaljenost zgornje cevi od gonilne osi (mm)	624,6	624,6	662,1	662,1
Doseg (mm)	390,6	398,7	394,5	414,5
Višina zgornje cevi (mm)	411	403	396,5	419
Širina krmila (mm)	690	690	690	690
Dolžina opore krmila (mm)	90	90	110	110
Dolžina gonilke (mm)	170	170	170	170
Velikost obročnikov	584X62	584X62	584X62	584X62

Vse navedene specifikacije se lahko spremenijo brez obvestila.