

ANYTOUR X E+ 3



SPECS

HYBRID CYKELTEKNIK	
MOTOR	Giant SyncDrive Sport2, 75Nm, PedalPlus 6-sensor technology
KONTROLLER	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
VISA	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERI	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
LADDARE	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Pyrite Brown / Black, Snow Drift / Black
RAM	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27,5" Frame-set, KSA40 Kickstand
GAFFEL	SR Suntour XCR32 ATB LO 27.5" Coil 100mm
BAKDÄMPARE	n/a
KOMPONENTER	
STYRE	Giant Contour Comfort Riser 31.8x690mm
GREPPAR	Giant Comfort Ergo Microtech Plus Lock-on
STAM	Giant Contour, EVO integrated, high adjustable
SADELSTOLPE	Suspension 2-bolt micro-adjustable, 30,9x270mm
SADEL	Selle Royal Vivo Ergo Unisex
PEDALER	VP VP537, PP platform / Anti-slip
DRIVLINJA	
VÄXLAR	Shimano Deore 10-speed
FRAMVÄXEL	n/a
BAKVÄXEL	Shimano Deore, 10-speed, Shadow+
BROMSAR	Shimano BR-MT200, hydraulic disc, 180mm
BROMSSPAKAR	Shimano BL-MT200
KASSETT	Shimano Deore, CS-M4100, 11-46T, 10-speed
KEDJA	KMC e.10 Sport, e-bike optimized
VEVPARTI	Alluminum 42T
BROMSREGLAGE	n/a

HJUL	
FÄLGAR	Giant eX25, Tubeless Ready, 584x25 Aluminium
NAV	Shimano HB-MT200 100x9mm QR Disc [F] Shimano FH-QC400-HM [R]
EKRAR	Stainless
DÄCK	Schwalbe Smart Sam Plus 57-584 (27.5 x 2.25"), DD, GreenGuard, ADDIX, E-50
EXTRAFUNKTIONER	KSA40 direct mount kickstand
TILLBEHÖR	
BELYSNING	Giant Recon HL50, 50 lux [F]AXA Juno 6-12V E-bike tail light [R]
LÅSA	ABUS Xplus Battery Lock / Abus 5755L XPlus NR
BÄRARE	MIK HD rack. System bag & basket compatible

Price: 44 690,00 kr

GEOMETRY

RAM	S	M	L	XL
Längd sadelrör (mm)	340	410	480	550
Vinkel sadelrör	74,0°	73,0°	72,0°	72,0°
Topprörets längd (mm)	570	590	610	630
Styrhuvud Längd (mm)	130	130	170	170
Vinkel styrhuvud	69,5°	69,5°	69,5°	69,5°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	87	87	87	87
Hjulbas (mm)	1120	1128	1138	1158
Kedjestagslängd (mm)	470	470	470	470
Nedre fäste Drop (mm)	50	50	50	50
Stack (mm)	625	625	662	662
Reach (mm)	391	399	395	415
Stå över höjden (mm)	592	564	524	488
Styrets bredd (mm)	690	690	690	690
Stamlängd (mm)	90	90	110	110
Vevlängd (mm)	170	170	170	170
Hjulstorlek	27.5"	27.5"	27.5"	27.5"

All specifications listed are subject to change without notice.