

CONTEND 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Icicle White
OKVIR	ALUXX-grade aluminum
VILICE	Advanced-grade composite, full-composite OverDrive steerer
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Connect XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Velo cork tape
OPORA KRMILA	Giant Sport XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:110mm
OPORA SEDEŽA	Giant D-Fuse, alloy, 14mm offset
SEDEŽ	Giant Approach
POGON	
PRESTAVNE ROČICE	Shimano CUES U3030
PREDNJI MENJALNIK	Shimano CUES U6030F
ZADNJI MENJALNIK	Shimano CUES U4020
ZAVORE	Tektro TK-B177
ZAVORNE ROČICE	Shimano U3030
VERIŽNIK	Shimano CS-LG300, 11x36
VERIGA	KMC X11
GONILKE Z VERIŽNIKI	Shimano FC-U6030-2, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano BB-RS501

OBROČNIKI	
OBROČI	Giant S-R3 wheelset, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	CST Sprint, 700x28c (30mm)
DODATKI	28mm max tire size
LIMITS	
MAX TIRE CLEARANCE	28mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	430	465	500	535	555	585
Kot sedežne cevi	74,8°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	515	530	545	560	575	595
Višina glave okvirja (mm)	123	138	158	178	198	218
Krmilni kot	71,0°	71,8°	72,5°	72,5°	72,5°	72,5°
Zamik vpetja osi (mm)	50	50	50	50	50	50
Trail (mm)	66,8	61,9	57,1	57,1	57,1	57,1
Medosna razdalja (mm)	985	986	990	1002	1017	1031
Dolžina cevi ob verigi (mm)	412	412	412	412	412	412
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	524	541	563	577	596	615
Doseg (mm)	372	375	378	384	393	401
Višina zgornje cevi (mm)	720	746	774	803	821	844
Širina krmila (mm)	400	400	420	420	440	440
Dolžina opore krmila (mm)	80	90	100	100	110	110
Dolžina gonilke (mm)	170	170	172,5	172,5	175	175

Vse navedene specifikacije se lahko spremenijo brez obvestila.