



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Metallic Black, Cobalt
CUADRO	ALUXX-grade aluminum
TIJERA	alloy, OverDrive steerer
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Connect XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Velo cork tape
POTENCIA	Giant Sport XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:110mm
POSTE DE ASIENTO	Giant D-Fuse, alloy, 14mm offset
ASIENTO	Giant Approach o Giant Grit Core
PEDALES	platform pedal [GU,GV,GJ] pedal with toe clips/straps [rest of GSC]
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Claris
DESVIADOR	Shimano Claris
CAMBIO TRASERO	Shimano Claris
FRENOS	Tektro TK-B177
PALANCAS DE FRENOS	Shimano Claris
CASSETTE	Shimano CS-HG50, 11x34
CADENA	KMC Z72
MULTIPLICACIÓN	FSA Tempo, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	cartridge

RUEDAS	
RUEDAS	Giant S-R3 wheelset, alloy
MAZAS	Giant alloy
RAYOS	stainless
NEUMÁTICOS	Giant S-R3-AC, 700x28c (30mm)
EXTRAS	28mm max tire size

Precio: \$18,990.00

GEOMETRÍA

CUADRO	XS	S	M	ML	L	XL
Longitud de la Base del Poste de Asiento (mm)	430	465	500	535	555	585
Ángulo de la Base del Poste de Asiento	74.8°	74.0°	73.5°	73.0°	73.0°	72.5°
Longitud del Tubo Superior (mm)	515	530	545	560	575	595
Longitud del Telescopio (mm)	123	138	158	178	198	218
Ángulo del Telescopio	71.0°	71.8°	72.5°	72.5°	72.5°	72.5°
Rake (mm)	50	50	50	50	50	50
Trail (mm)	66.8	61.9	57.1	57.1	57.1	57.1
Distancia entre Ejes (mm)	985	986	990	1002	1017	1031
Longitud de Vaina Inferior (mm)	412	412	412	412	412	412
Caída del Eje de Centro (mm)	75	75	75	70	70	70
Stack (mm)	524	541	563	577	596	615
Reach (mm)	372	375	378	384	393	401
Altura del Tubo Superior al Suelo (mm)	720	746	774	803	821	844
Ancho del Manubrio (mm)	400	400	420	420	440	440
Longitud de la Potencia (mm)	80	90	100	100	110	110
Longitud de la Biela (mm)	170	170	172.5	172.5	175	175
Tamaño de las Ruedas	700C	700C	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.