

CONTEND AR 1

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Abyss Black
CUADRO	ALUXX-grade aluminum, 12x142mm thru-axle, disc
TIJERA	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant D-Fuse SL XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Velo cork tape with gel
POTENCIA	Giant Contact XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
POSTE DE ASIENTO	Giant D-Fuse, composite, 14mm offset
ASIENTO	Giant Approach
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano 105
DESVIADOR	Shimano 105
CAMBIO TRASERO	Shimano 105 GS
FRENOS	Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	Shimano 105
CASSETTE	Shimano 105, 12-speed, 11x36
CADENA	KMC X12L-1
MULTIPLICACIÓN	Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
EJE DE CENTRO	Shimano BB-RS501

RUEDAS	
RUEDAS	Giant P-R2 Disc wheelset, alloy, [F]25mm, [R]25mm
MAZAS	Giant alloy, 12mm thru-axle
RAYOS	Sapim
NEUMÁTICOS	Giant Gavia Fondo 2, tubeless, 700x32c (34mm)
EXTRAS	fender mount, tubeless prepared, 38mm max tire size
LIMITS	
MAX TIRE CLEARANCE	38mm

Precio: \$45,990.00

GEOMETRÍA

CUADRO	XS	S	M	ML	L	XL
Longitud de la Base del Poste de Asiento (mm)	430	465	500	535	555	585
Ángulo de la Base del Poste de Asiento	75.0°	74.0°	73.5°	73.0°	73.0°	73.0°
Longitud del Tubo Superior (mm)	515	535	550	565	580	595
Longitud del Telescopio (mm)	115	135	150	170	190	215
Ángulo del Telescopio	71.5°	71.8°	72.0°	72.5°	72.5°	72.5°
Rake (mm)	53	53	53	53	53	53
Trail (mm)	62.9	61.3	59.6	56.4	56.4	56.4
Distancia entre Ejes (mm)	994	1003	1011	1015	1031	1046
Longitud de Vaina Inferior (mm)	422	422	422	422	422	422
Caída del Eje de Centro (mm)	80	80	80	80	80	80
Stack (mm)	539	559	574	595	614	638
Reach (mm)	371	375	380	383	392	400
Altura del Tubo Superior al Suelo (mm)	727	759	783	810	829	856
Ancho del Manubrio (mm)	400	400	420	420	440	440
Longitud de la Potencia (mm)	80	90	100	100	110	110
Longitud de la Biela (mm)	165	165	170	170	172.5	172.5

Todas las especificaciones están sujetas a cambios sin previo aviso.