

# CONTEND AR 1

**GIANT**



## SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Abyss Black
RAMME	ALUXX-grade aluminum, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Giant D-Fuse SL XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Velo cork tape with gel
STYRSTEM	Giant Contact XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SETEPINNE	Giant D-Fuse, composite, 14mm offset
SADEL	Giant Approach
DRIVVERK	
GIRHENDLER	Shimano 105
FRONTGIR	Shimano 105
BAKGIR	Shimano 105 GS
BREMSE	Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSEHENDLER	Shimano 105
KASSETT	Shimano 105, 12-speed, 11x36
KJEDE	KMC X12L-1
KRANK	Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano BB-RS501

HJUL	
FELG	Giant P-R2 Disc wheelset, alloy, [F]25mm, [R]25mm
NAV	Giant alloy, 12mm thru-axle
EIKE	Sapim
DEKK	Giant Gavia Fondo 2, tubeless, 700x32c (34mm)
EXTRAS	fender mount, tubeless prepared, 38mm max tire size
LIMITS	
MAX TIRE CLEARANCE	38mm

## GEOMETRI

RAMME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	430	465	500	535	555	585
Seat Tube Angle	75,0°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	535	550	565	580	595
Head Tube Length (mm)	115	135	150	170	190	215
Head Tube Angle	71,5°	71,8°	72,0°	72,5°	72,5°	72,5°
Fork Rake (mm)	53	53	53	53	53	53
Trail (mm)	62,9	61,3	59,6	56,4	56,4	56,4
Wheelbase (mm)	994	1003	1011	1015	1031	1046
Chain Stay Length (mm)	422	422	422	422	422	422
Bottom Bracket Drop (mm)	80	80	80	80	80	80
Stack (mm)	539	559	574	595	614	638
Reach (mm)	371	375	380	383	392	400
Stand Over Height (mm)	727	759	783	810	829	856
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	100	110	110
Crank Length (mm)	165	165	170	170	172,5	172,5

Alle spesifikasjonene kan endres uten varsel.