



## ŠPECIFIKÁCIE

| RÁM               |  |
|-------------------|--|
| VELKOSTI          | XS, S, M, M/L, L, XL   |
| FARBY             | Abyss Black  |
| RÁM               | ALUXX-grade aluminum, 12x142mm thru-axle, disc                                       |
| VIDLICA           | Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc |
| TLMIČ             | N/A  |
| KOMPONENTY        |  |
| RIADIDLÁ          | Giant D-Fuse SL XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm                   |
| GRIPY             | Velo cork tape with gel  |
| PREDSTAVEC        | Giant Contact XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm                 |
| SEDLOVKA          | Giant D-Fuse, composite, 14mm offset   |
| SEDADLO           | Giant Approach   |
| POHON             |  |
| RADENIE           | Shimano 105  |
| PREŠMYKAČ         | Shimano 105  |
| PREHADZOVAČKA     | Shimano 105 GS   |
| BRZDY             | Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]160mm                           |
| BRZDOVÉ PÁKY      | Shimano 105  |
| KAZETA            | Shimano 105, 12-speed, 11x36   |
| REŤAZ             | KMC X12L-1   |
| KLUKY             | Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm      |
| STREDOVÉ ZLOŽENIE | Shimano BB-RS501   |

| KOLESÁ                    |   |
|---------------------------|---|
| RÁFIKY                    | Giant P-R2 Disc wheelset, alloy, [F]25mm, [R]25mm   |
| NÁBOJE                    | Giant alloy, 12mm thru-axle                         |
| ŠPICE                     | Sapim   |
| PNEUMATIKY                | Giant Gavia Fondo 2, tubeless, 700x32c (34mm)       |
| DOPLNKY                   | fender mount, tubeless prepared, 38mm max tire size |
| LIMITY                    |   |
| MAXIMÁLNA ŠÍRKA PNEUMATÍK | 38mm  |

Cena: 1 799 €

## GEOMETRIA

| RÁM  | XS    | S     | M     | ML    | L     | XL    |
|--|-------|-------|-------|-------|-------|-------|
| Dĺžka sedlovej trubky (mm)                       | 430   | 465   | 500   | 535   | 555   | 585   |
| Uhol sedlovej trubky                             | 75,0° | 74,0° | 73,5° | 73,0° | 73,0° | 73,0° |
| Dĺžka hornej rámovej trubky (mm)                 | 515   | 535   | 550   | 565   | 580   | 595   |
| Dĺžka hlavovej trubky (mm)                       | 115   | 135   | 150   | 170   | 190   | 215   |
| Uhol hlavovej trubky                             | 71,5° | 71,8° | 72,0° | 72,5° | 72,5° | 72,5° |
| Offset vidlice (mm)                              | 53    | 53    | 53    | 53    | 53    | 53    |
| Trail (mm)                                       | 62,9  | 61,3  | 59,6  | 56,4  | 56,4  | 56,4  |
| Rázvor (mm)                                      | 994   | 1003  | 1011  | 1015  | 1031  | 1046  |
| Dĺžka zadnej stavby (mm)                         | 422   | 422   | 422   | 422   | 422   | 422   |
| Rozdiel zadnej voči stredovej osi - BB DROP (mm) | 80    | 80    | 80    | 80    | 80    | 80    |
| Stack - výška riadenia (mm)                      | 539   | 559   | 574   | 595   | 614   | 638   |
| Reach (mm)                                       | 371   | 375   | 380   | 383   | 392   | 400   |
| Výška rámu od zeme (mm)                          | 727   | 759   | 783   | 810   | 829   | 856   |
| Šírka riaditok (mm)                              | 400   | 400   | 420   | 420   | 440   | 440   |
| Dĺžka predstavca (mm)                            | 80    | 90    | 100   | 100   | 110   | 110   |
| Dĺžka klúku (mm)                                 | 165   | 165   | 170   | 170   | 172,5 | 172,5 |

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.