

CONTEND AR 2



SPECS

FRAME	
SIZES	XS, S, M, ML, L, XL
COLORS	Luminous Lagoon/Pearl White
FRAME	ALUXX-SL Grade Aluminum 12x142mm thru-axle, Disc
FORK	Advanced-Grade Composite, Full Carbon, OverDrive Steerer, 12x100mm thru-axle, Disc
COMPONENTS	
HANDLEBAR	Giant Contact (w/Flare) Reach 72mm & Drop 125mm
GRIPS	Cork Tape VLT-004
STEM	Giant Contact Aerolight
SEATPOST	Giant D-Fuse Composite Offset 14mm
SADDLE	Giant Approach 7mm Steel Rail, with UniClip / ParticleFlow technology
PEDALS	platform pedal [GU,GV,GJ] pedal with toe clips/straps [rest of GSC]
DRIVETRAIN	
SHIFTERS	Shimano CUES U6030
FRONT DERAILLEUR	Shimano Cues U6030
REAR DERAILLEUR	Shimano Cues U6020-10
BRAKES	Shimano BR-U6030 [F]160 [R]160
BRAKE LEVERS	Shimano Cues U6030
CASSETTE	Shimano CS-LG400, 11X39, 10 speed
CHAIN	KMC X11
CRANKSET	Shimano FC-U6030-2, 50/34
BOTTOM BRACKET	Shimano BB-R5501

WHEELS	
RIMS	Giant P-AR, 12mm Thru-Axle
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Fondo 2, 700X32C Tubeless

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	430	465	500	535	555	585
Seat Tube Angle	75,0°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	535	550	565	580	595
Head Tube Length (mm)	115	135	150	170	190	215
Head Tube Angle	71,5°	71,8°	72,0°	72,5°	72,5°	72,5°
Fork Rake (mm)	53	53	53	53	53	53
Trail (mm)	62,9	61,3	59,6	56,4	56,4	56,4
Wheelbase (mm)	994,4	1002,8	1010,6	1015,4	1030,6	1045,8
Chain Stay Length (mm)	422	422	422	422	422	422
Bottom Bracket Drop (mm)	80	80	80	80	80	80
Stack (mm)	539,2	559,1	574,3	595,3	614,4	638,2
Reach (mm)	370,5	374,7	379,9	383	392,2	399,9
Stand Over Height (mm)	717,5	743,7	770,1	798,5	817	843,9
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	100	110	110
Crank Length (mm)	165	165	170	170	172,5	172,5
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.