

CONTEND AR 2



SPECIFICATIES

FRAME	
MATEN	S, M, ML, L, XL
KLEUREN	Luminous Lagoon/Pearl White
FRAME	ALUXX-SL Grade Aluminum 12x142mm thru-axle, Disc
VOORVORK	Advanced-Grade Composite, Full Carbon, OverDrive Steerer, 12x100mm thru-axle, Disc
ONDERDELEN	
STUUR	Giant Contact (w/Flare) Reach 72mm & Drop 125mm
HANDVATTEN	Cork Tape VLT-004
STUURPEN	Giant Contact Aerolight
ZADELPEN	Giant D-Fuse Composite Offset 14mm
ZADEL	Giant Approach 7mm Steel Rail, with UniClip / ParticleFlow technology
PEDALEN	-
AFMONTAGE	
SHIFTERS	Shimano CUES U6030
VOORDERAILLEUR	Shimano Cues U6030
ACHTERDERAILLEUR	Shimano Cues U6020-10
REMMEN	Shimano BR-U6030 [F]160 [R]160
REMHENDELS	Shimano Cues U6030
CASSETTE	Shimano CS-LG400, 11X39, 10 speed
AANDRIJVING	KMC X11
CRANKSET	Shimano FC-U6030-2, 50/34
BOTTOM BRACKET	Shimano BB-R5501

WIELSET	
VELGEN	Giant P-AR, 12mm Thru-Axle
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	Sapim
BANDEN	Giant Gavia Fondo 2, 700X32C Tubeless

Adviesprijs: € 1.599,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	465	500	535	555	585
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	535	550	565	580	595
Balhoofdbuis Lengte (mm)	135	150	170	190	215
Balhoofdbuis Hoek	71,8°	72,0°	72,5°	72,5°	72,5°
Vork Sprong (mm)	53	53	53	53	53
Naloop (mm)	61,3	59,6	56,4	56,4	56,4
Wielbasis (mm)	1002,8	1010,6	1015,4	1030,6	1045,8
Liggende achtervork lengte (mm)	422	422	422	422	422
Bottom Bracket Drop (mm)	80	80	80	80	80
Stack (mm)	559,1	574,3	595,3	614,4	638,2
Reach (mm)	374,7	379,9	383	392,2	399,9
Stand Over Height (mm)	743,7	770,1	798,5	817	843,9
Stuur breedte (mm)	400	420	420	440	440
Stuurpen Lengte (mm)	90	100	100	110	110
Cranklengte (mm)	165	170	170	172,5	172,5
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.