

CONTEND AR 2

GIANT



TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Dark Iridescent
CADRE	ALUXX-grade aluminum, 12x142mm thru-axle, disc
FOURCHE	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Connect XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
POIGNÉES	Velo cork tape with gel
POTENCE	Giant Sport XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:110mm
TIGE DE SELLE	Giant D-Fuse, composite, 14mm offset
SELLE	Giant Approach
PÉDALES	Pedal with toe clips/straps
DÉRAILLEUR	
MANETTES	Shimano Tiagra
DÉRAILLEUR AVANT	Shimano Tiagra
DÉRAILLEUR ARRIÈRE	Shimano Tiagra GS
FREINS	Shimano Tiagra, Giant MPH rotors [F]160mm, [R]160mm
LEVIERS DE FREIN	Shimano Tiagra
CASSETTE	Shimano Tiagra, 11x34
CHAÎNE	KMC X10-1
PÉDALIER	Shimano Tiagra, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOITIER DE PÉDALIER	cartridge

ROUES	
JANTES	Giant S-R2 Disc wheelset, alloy
MOYEURS	Giant alloy, 12mm thru-axle
RAYONS	Sapim
PNEUS	Giant Gavia Fondo 2, tubeless, 700x32c (34mm)
EXTRAS	fender mount, tubeless prepared, 38mm max tire size
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
DÉGAGEMENT MAX DES PNEUS	38mm

Prix Public Conseillé: 1 600,00 €

GÉOMÉTRIE

CADRE	XS	S	M	ML	L	XL
Longueur de tube de selle (mm)	410	445	480	515	535	565
Angle de tube de selle	75,0°	74,0°	73,5°	73,0°	73,0°	73,0°
Longueur du tube supérieur (mm)	515	535	550	565	580	595
Longueur du tube de direction (mm)	115	135	150	170	190	215
Angle du tube de direction	71,5°	71,8°	72,0°	72,5°	72,5°	72,5°
Déport de fourche (mm)	53	53	53	53	53	53
Trail (mm)	62,9	61,3	59,6	56,4	56,4	56,4
Empattement (mm)	994	1003	1011	1015	1031	1046
Longueur des bases (mm)	422	422	422	422	422	422
Drop du boîtier de pédalier (mm)	80	80	80	80	80	80
Stack (mm)	539	559	574	595	614	638
Reach (mm)	371	375	380	383	392	400
Hauteur en statique (mm)	727	759	783	810	829	856
Largeur de cintre (mm)	400	400	420	420	440	440
Longueur de potence (mm)	80	90	100	100	110	110
Longueur des manivelles (mm)	170	170	172,5	172,5	175	175
Diamètre des roues	700C	700C	700C	700C	700C	700C

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.