



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Dark Iridescent, Solar Flare
OKVIR	ALUXX-grade aluminum, 12x142mm thru-axle, disc
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Connect XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Velo cork tape with gel
OPORA KRMILA	Giant Sport XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:110mm
OPORA SEDEŽA	Giant D-Fuse, composite, 14mm offset
SEDEŽ	Giant Approach
PEDALA	platform pedal [GU,GV,GJ] pedal with toe clips/straps [rest of GSC]
POGON	
PRESTAVNE ROČICE	Shimano Tiagra
PREDNJI MENJALNIK	Shimano Tiagra
ZADNJI MENJALNIK	Shimano Tiagra GS
ZAVORE	Shimano Tiagra, Giant MPH rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano Tiagra
VERIŽNIK	Shimano Tiagra, 11x34
VERIGA	KMC X10-1
GONILKE Z VERIŽNIKI	Shimano Tiagra, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	cartridge

OBROČNIKI	
OBROČI	Giant S-R2 Disc wheelset, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	Giant Gavia Fondo 2, tubeless, 700x32c (34mm)
DODATKI	fender mount, tubeless prepared, 38mm max tire size
LIMITS	
MAX TIRE CLEARANCE	38mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	410	445	480	515	535	565
Kot sedežne cevi	75,0°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	535	550	565	580	595
Višina glave okvirja (mm)	115	135	150	170	190	215
Krmilni kot	71,5°	71,8°	72,0°	72,5°	72,5°	72,5°
Zamik vpetja osi (mm)	53	53	53	53	53	53
Trail (mm)	62,9	61,3	59,6	56,4	56,4	56,4
Medosna razdalja (mm)	994	1003	1011	1015	1031	1046
Dolžina cevi ob verigi (mm)	422	422	422	422	422	422
Bottom Bracket Drop (mm)	80	80	80	80	80	80
Oddaljenost zgornje cevi od gonilne osi (mm)	539	559	574	595	614	638
Doseg (mm)	371	375	380	383	392	400
Višina zgornje cevi (mm)	727	759	783	810	829	856
Širina krmila (mm)	400	400	420	420	440	440
Dolžina opore krmila (mm)	80	90	100	100	110	110
Dolžina gonilke (mm)	170	170	172,5	172,5	175	175
Velikost obročnikov	700C	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.