CONTEND AR 3



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Icicle White
FRAME	ALUXX-grade aluminium, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Giant
STEM	Giant Sport XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SEATPOST	Giant D-Fuse, alloy, 14mm offset
SADDLE	Giant Approach
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano CUES U3030
FRONT DERAILLEUR	Shimano Cues U6030F
REAR DERAILLEUR	Shimano Cues U4020-9
BRAKES	Tektro MD-C550 mechanical, Giant MPH Rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano U3030
CASSETTE	Shimano CS-LG300, 9-speed, 11x36
CHAIN	KMC X11
CRANKSET	Shimano Cues FCU6030-2, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano BB-RS501

WHEELS	
RIMS	Giant S-R2 Disc wheelset, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TYRES	CST Sprint, 700x33c
EXTRAS	38mm max tyre size
LIMITS	
MAX TYRE CLEARANCE	38mm

Price: $1,799.00

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	430	465	500	535	555	585
Seat Tube Angle	75.0°	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	515	535	550	565	580	595
Head Tube Length (mm)	115	135	150	170	190	215
Head Tube Angle	71.5°	71.8°	72.0°	72.5°	72.5°	72.5°
Fork Rake (mm)	53	53	53	53	53	53
Trail (mm)	62.9	61.3	59.6	56.4	56.4	56.4
Wheelbase (mm)	994	1003	1011	1015	1031	1046
Chain Stay Length (mm)	422	422	422	422	422	422
Bottom Bracket Drop (mm)	80	80	80	80	80	80
Stack (mm)	539	559	574	595	614	638
Reach (mm)	371	375	380	383	392	400
Stand Over Height (mm)	727	759	783	810	829	856
Stem Length (mm)	80	90	100	100	110	110
Crank Length (mm)	165	165	170	170	172.5	172.5

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.*