

CONTEND SL 0

GIANT



SPECS

QUADRO	
TAMANHOS	XS, S, M, M/L, L
CORES	Pearl White/Charcoal
QUADRO	ALUXX-SL Grade Aluminum 12x142mm Thru-axle, Disc
FORQUILHA	Advanced-Grade Composite, Full Carbon, OverDrive Steerer, 12x100mm thru-axle, Disc
COMPONENTES	
GUIADOR	Giant Contact (w/Flare) Drop: 125mm / Reach: 72m
PUNHOS	Cork Tape VLT-001G
AVANÇO	Giant Contact Aerolight
ESPIGÃO DE SELIM	AL D-fuse SP-2056, 350mm
SELIM	Giant Grit Core
TRANSMISSÃO	
MANETES	Shimano 105
DESVIADOR DIANTEIRO	Shimano 105
DESVIADOR TRASEIRO	Shimano 105
TRAVÕES	Shimano 105 Hydraulic Disc Brake [F]160mm [R]140mm
MANÍPULOS DOS TRAVÕES	Shimano 105
CASSETTE	Shimano 105, 11X36T
CORRENTE	KMC X12L-1
CONJUNTO PEDALEIRO	Shimano 105, 50/34T
MOVIMENTO CENTRAL	Shimano, PressFit RS500

RODAS	
AROS	Giant ALP Disc 12mm Thru-Axle
PNEUS	Giant SR 1 700X28C, 60 TPI

Preço: 1 599,00 €

GEOMETRIA

QUADRO	XS	S	M	ML	L
Comprimento do tubo do assento (mm)	410	445	480	515	535
Ângulo do tubo do assento	74,5°	74,0°	73,5°	73,0°	73,0°
Comprimento do tubo superior (mm)	515	530	545	560	575
Comprimento do tubo principal (mm)	125	135	150	175	195
Ângulo do tubo principal	70,5°	71,8°	72,5°	72,5°	72,5°
Garfo ancinho (mm)	50	50	50	50	50
Trilha (mm)	71,1	62,9	58,1	58,1	58,1
distância entre eixos (mm)	995,2	994,4	997,7	1010	1025,2
Comprimento Chain Stay (mm)	420	420	420	420	420
Suporte inferior (mm)	75	75	75	70	70
Pilha (mm)	526,8	540,8	557,8	576,6	595,7
Alcançar (mm)	368,9	374,9	379,8	383,7	392,9
Altura do standover (mm)	689,3	716,3	744	777,5	796
Largura do guidão (mm)	400	400	420	420	440
Comprimento da haste (mm)	80	90	100	100	110
Comprimento da Manivela (mm)	170	170	172,5	175	175
Tamanho da roda	700C	700C	700C	700C	700C

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.