

CONTEND SL 1



TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Pearl White/Brushed Chrome
CADRE	ALUXX-SL Grade Aluminum 12x142mm thru-axle, Disc
FOURCHE	Advanced-Grade Composite, Full Carbon, OverDrive Steerer, 12x100mm thru-axle, Disc
COMPOSANTS	
CINTRE	Giant Contact (w/Flare) Drop: 125mm / Reach: 72mm
POIGNÉES	Cork (Gel) Tape VLT-001G
POTENCE	Giant Contact Aerolight, -10° XS: 80, S: 90, M: 100, M/L: 100, L:110, XL: 120
TIGE DE SELLE	Giant D-Fuse Composite Offset 14mm
SELLE	Giant Grit Core
DÉRAILLEUR	
MANETTES	Shimano Tiagra R4000
DÉRAILLEUR AVANT	Shimano Tiagra R4000
DÉRAILLEUR ARRIÈRE	Shimano Tiagra R4000
FREINS	Shimano Tiagra Hydraulic Disc Brake [F]160mm [R]140mm
LEVIER DE FREIN	Shimano Tiagra R4000
CASSETTE	Shimano CS-RS400-11, 11X36, 11 speed
CHAÎNE	KMC X11
PÉDALIER	Shimano FC-R4000, 50/34
BOITIER DE PÉDALIER	Shimano, PressFit RS500

ROUES	
JANTES	Giant ALP Disc 12mm Thru-Axle
PNEUS	Giant SR 1 700X28C, 60 TPI
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
DÉGAGEMENT MAX DES PNEUS	700x33mm

Prix Public Conseillé: 1 600,00 €

GÉOMÉTRIE

CADRE	XS	S	M	ML	L	XL
Longueur de tube de selle (mm)	410	445	480	515	535	565
Angle de tube de selle	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Longueur du tube supérieur (mm)	515	530	545	560	575	590
Longueur du tube de direction (mm)	125	135	150	175	195	215
Angle du tube de direction	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Déport de fourche (mm)	50	50	50	50	50	50
Trail (mm)	71,1	62,9	58,1	58,1	58,1	58,1
Empattement (mm)	995,2	994,4	997,7	1010	1025,2	1040,4
Longueur des bases (mm)	420	420	420	420	420	420
Drop du boîtier de pédalier (mm)	75	75	75	70	70	70
Stack (mm)	526,8	540,8	557,8	576,6	595,7	614,8
Reach (mm)	368,9	374,9	379,8	383,7	392,9	402
Hauteur en statique (mm)	689,3	716,3	744	777,5	796	822
Largeur de cintre (mm)	400	400	420	420	440	420
Longueur de potence (mm)	80	90	100	100	110	110
Longueur des manivelles (mm)	170	170	172,5	175	175	175
Diamètre des roues	700C	700C	700C	700C	700C	700C

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.