

CONTEND SL 2



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Cryo Silver
FRAME	ALUXX SL-grade aluminum, disc
FORK	alloy, OverDrive steerer, disc
COMPONENTS	
HANDLEBAR	Giant Contact, flare XS:400/370mm, S:400/370mm, M:420/390mm, M/L:420/390mm, L:420/390mm, XL:420/390mm
GRIPS	Velo cork tape with gel
STEM	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SEATPOST	Giant D-Fuse, alloy
SADDLE	Giant Approach
DRIVETRAIN	
SHIFTERS	Shimano Sora
FRONT DERAILLEUR	Shimano Sora
REAR DERAILLEUR	Shimano Sora
BRAKES	Giant MPH hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano Sora
CASSETTE	Shimano CS-RS400, 9-speed, 11x34
CHAIN	KMC X9
CRANKSET	ProWheel, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	ProWheel, press fit

WHEELS	
RIMS	Giant ALP wheelset, alloy, [F]25mm, [R]25mm
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant SR 1, 700x28c (30mm)
EXTRAS	fender mount
LIMITS	
MAX TIRE CLEARANCE	32mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (inch)	16.1	17.5	18.9	20.3	21.1	22.2
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (inch)	20.3	20.9	21.5	22	22.6	23.2
Head Tube Length (inch)	4.9	5.3	5.9	6.9	7.7	8.5
Head Tube Angle	70.5°	71.8°	72.5°	72.5°	72.5°	72.5°
Fork Rake (inch)	2	2	2	2	2	2
Trail (inch)	2.8	2.4	2.3	2.3	2.3	2.3
Wheelbase (inch)	39.2	39.1	39.3	39.8	40.4	40.9
Chain Stay Length (inch)	16.5	16.5	16.5	16.5	16.5	16.5
Bottom Bracket Drop (inch)	3	3	3	2.8	2.8	2.8
Stack (inch)	20.7	21.3	21.9	22.7	23.4	24.2
Reach (inch)	14.5	14.7	14.9	15.1	15.4	15.8
Stand Over Height (inch)	27.1	28.2	29.3	30.6	31.3	32.4
Handlebar Width (inch)	15.7	15.7	16.5	16.5	17.3	16.5
Stem Length (inch)	3.1	3.5	3.9	3.9	4.3	4.3
Crank Length (inch)	6.5	6.5	6.7	6.7	6.8	6.8
Wheel Size	700C	700C	700C	700C	700C	700C

**All specifications and prices listed are subject to change without notice.
Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*