

CONTEND SL 2



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L
BARVE	Snow Drift, Charcoal
OKVIR	ALUXX-SL Grade Aluminum 12x142mm Thru-axle, Disc
VILICE	Alloy, OverDrive Steerer
KOMPONENTE	
KRMILO	Giant Contact (w/Flare) Drop: 125mm / Reach: 72mm
GRIPS	Cork Tape VLT-001
OPORA KRMILA	Giant Contact Aerolight
OPORA SEDEŽA	AL D-fuse SP-2056, 350mm
SEDEŽ	Giant Grit Core
POGON	
PRESTAVNE ROČICE	Shimano Sora
PREDNJI MENJALNIK	Shimano Sora
ZADNJI MENJALNIK	Shimano Sora
ZAVORE	Giant MPH Disc Brake [F]160mm [R]160mm
ZAVORNE ROČICE	Shimano
VERIŽNIK	Shimano CSHG400,11-34T
VERIGA	KMC X9
GONILKE Z VERIŽNIKI	Prowheel 50/34T
BOTTOM BRACKET	Shimano, PressFit RS500

OBROČNIKI	
OBROČI	Giant ALP Disc 12mm Thru-Axle
PLAŠČI	Giant SR 1 700X28C, 60 TPI

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	410	445	480	515	535	565
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	530	545	560	575	590
Višina glave okvirja (mm)	125	135	150	175	195	215
Krmilni kot	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Zamik vpetja osi (mm)	50	50	50	50	50	50
Trail (mm)	71,1	62,9	58,1	58,1	58,1	58,1
Medosna razdalja (mm)	995,2	994,4	997,7	1010	1025,2	1040,4
Dolžina cevi ob verigi (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	526,8	540,8	557,8	576,6	595,7	614,8
Doseg (mm)	368,9	374,9	379,8	383,7	392,9	402
Višina zgornje cevi (mm)	689,3	716,3	744	777,5	796	822
Širina krmila (mm)	400	400	420	420	440	420
Dolžina opore krmila (mm)	80	90	100	100	110	110
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5
Velikost obročnikov	700C	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.