

CUADRO ANTHEM ADVANCED SL SE WORLD CHAMPION





ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	SE World Champion
CUADRO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
AMORTIGUADOR	Fox Float SL Factory, 210/50 with custom "Alan Hatherly" compression tune
COMPONENTES	
MANILLAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
POTENCIA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm

RUEDAS	
EXTRAS	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Precio: 4.199,00 €

GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud del tubo del sillín (mm)	400		420		465		495	
Ángulo del tubo del sillín	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Longitud del tubo superior (mm) (mm)	576	574	602	600	624	623	651	650
Longitud del tubo de dirección (mm) (mm)	90		95		105		115	
Ángulo del tubo de dirección	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Inclinación de la horquilla (mm)	44		44		44		44	
Trail (mm) (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
Distancia entre ejes (mm) (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Longitud de la vaina (mm) (mm)	437	435	437	435	437	435	437	435
Caída del eje de pedalier (mm) (mm)	51	45	51	45	52	45	52	45
Stack (mm) (mm)	602	599	607	603	616	612	626	622
Reach (mm) (mm)	420	425	445	450	465	470	490	495
Altura del suelo al tubo (mm) (mm)	769	775	764	771	758	763	751	758
Ancho del manillar (mm) (mm)	780		780		780		780	
Longitud de la potencia (mm) (mm)	60		70		70		80	
Longitud de las bielas (mm) (mm)	170		170		175		175	

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.