

CUADRO PROPEL ADVANCED SL

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Cosmic Dust - Holi Flare
CUADRO	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
HORQUILLA	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
TIJA DE SILLÍN	Advanced SL-grade composite, integrated design, -5/+15mm offset

RUEDAS	
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	32mm

Precio: 3.999,00 €

GEOMETRÍA

CUADRO	XS	S	M	ML	L	XL
Longitud del tubo del sillín (mm)	680	710	740	770	800	830
Ángulo del tubo del sillín	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longitud del tubo superior (mm) (mm)	520	535	550	565	580	600
Longitud del tubo de dirección (mm) (mm)	120	130	145	165	185	200
Ángulo del tubo de dirección	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Inclinación de la horquilla (mm)	45	45	45	45	45	45
Trail (mm) (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Distancia entre ejes (mm) (mm)	976	977	980	991	1006	1020
Longitud de la vaina (mm) (mm)	405	405	405	405	405	405
Caída del eje de pedaliador (mm) (mm)	72	70	70	67	67	67
Stack (mm) (mm)	517	528	545	562	581	596
Reach (mm) (mm)	376	383	388	393	402	412
Altura del suelo al tubo (mm) (mm)	734	755	775	794	821	834
Ancho del manillar (mm) (mm)	400	400	420	420	440	440
Longitud de la potencia (mm) (mm)	80	90	100	110	110	120
Longitud de las bielas (mm) (mm)	170	170	172,5	172,5	175	175
Tamaño de ruedas	700C	700C	700C	700C	700C	700C

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.