

CUADRO REIGN ADVANCED

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Rainbow Sprayed
CUADRO	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
AMORTIGUADOR	Fox Float X2 Factory, 205/62.5, custom tuned for Giant

Precio: 4.499,00 €

GEOMETRÍA

CUADRO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Longitud del tubo del sillín (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	262			287			312			337
Ángulo del tubo del sillín	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°
Longitud del tubo superior (mm) (mm)	556 555 555			587 586 585			620 620 619			652
Longitud del tubo de dirección (mm) (mm)	100			105			115			120
Ángulo del tubo de dirección	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°
Inclinación de la horquilla (mm)	44			44			44			44
Trail (mm) (mm)	140 138 135			140 138 135			140 138 135			140
Distancia entre ejes (mm) (mm)	1214 1213 1212			1246 1245 1244			1271 1270 1269			1304
Longitud de la vaina (mm) (mm)	445 443 442			445 443 442			445 443 442			445
Caída del eje de pedaliador (mm) (mm)	35 30 25			35 30 25			35 30 25			35
Stack (mm) (mm)	627 624 622			632 629 626			641 638 635			645
Reach (mm) (mm)	426 430 434			456 460 464			476 480 484			506
Altura del suelo al tubo (mm) (mm)	720 724 729			735 739 744			751 756 760			746
Ancho del manillar (mm) (mm)	800			800			800			800
Longitud de la potencia (mm) (mm)	40			40			40			40
Longitud de las bielas (mm) (mm)	165			170			170			170
Tamaño de ruedas	29"			29"			29"			29"

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.