

DAILYTOUR E+ 0



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport, 70Nm, powered by Yamaha, PedalPlus 6-sensor technology
BEDIENINGSUNIT	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideDash EVO, high-angle visibility, 3" full color LCD display
ACCU	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
LADER	Giant EnergyPak 6A smart charger, 60% charge in 3:00h
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	S, M, L
KLEUREN	Cobalt
FRAME	ALUXX SL aluminum
VOORVORK	SR Suntour MOBIE 25 AIR LO, 63mm, 15x100mm Axle
ONDERDELEN	
STUUR	Giant Contour GT, cable integrated, 30° back sweep 31.8mm
HANDVATTEN	Connect Ergo Max Sweep
STUURPEN	Giant Contour, EVO display integrated, adjustable
ZADEL	Selle Royal Look-In gel
PEDALEN	Aluminum, VP-183
AFMONTAGE	
SHIFTERS	Enviolo Automatiq Pure Controller
REMMEN	Shimano BR-MT410, hydraulic disc, 160mm [F&R]
REMHENDELS	Shimano BL-MT401
CASSETTE	Gates CDXtm stainless steel 22T rear sprocket
AANDRIJVING	Gates CDXtm Carbon Drive 122T CenterTrack belt
CRANKSET	Gates CDXtm CenterTrack 46T front sprocket

WIELSET	
VELGEN	Giant eX 2, Tubeless Ready, 700c Aluminium
NAVEN	Giant eTracker, [F] 100x15 [F], Enviolo Automatiq TR Disc brake [R]
SPAKEN	Sapim Race [F], Sapim Strong [R]
BANDEN	Schwalbe Marathon E Plus 622x50, Smart DualGuard Addix E
ACCESSOIRES	
VERLICHTING	Giant Numen iD integrated day-time LED, Axa Blueline 30 automatic front LED, Axa Blueline rear LED
SLOT	Abus Pro Amparo 4750X R
DRAGER	MIK rack. System bag & basket compatible

Adviesprijs: € 4.999,00

GEOMETRIE

FRAME	S	M	L
Zitbuis Lengte (mm)	450	500	550
Zitbuis Hoek	72,5°	72,0°	72,0°
Frame Lengte (horizontaal) (mm)	580	595	610
Balhoofdbuis Lengte (mm)	160	170	185
Balhoofdbuis Hoek	69,5°	69,5°	69,5°
Vork Sprong (mm)	44	44	44
Naloop (mm)	86,9	86,9	86,9
Wielbasis (mm)	1108	1117	1133
Liggende achtervork lengte (mm)	470	470	470
Bottom Bracket Drop (mm)	60	60	60
Stack (mm)	634	643	657
Reach (mm)	380	386	396
Stand Over Height (mm)	407	400	395
Stuur breedte (mm)	670	670	670
Stuurpen Lengte (mm)	90	90	90
Cranklengte (mm)	170	170	170
Wielmaat	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.