

DAILYTOUR E+ 1 BD (GE) LDS



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDrive Core, 50Nm, Powered by Yamaha
TIPALO	RideControl Ergo 2
PRIKAZOVALNIK	RideDash Evo
BATERIJA	EnergyPak Smart 625Wh
OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	A: Metallic Navy, B: Black Diamond, C: Hematite
OKVIR	ALUXX Aluminum
VILICE	SR Suntour NEX E25, lockout, 63mm , 15AQ
KOMPONENTE	
KRMILO	Giant Contour GT, cable integrated, 30° back sweep 31.8mm
GRIPS	Connect Ergo Max Sweep
OPORA KRMILA	Giant Contour, EVO display integrated, adjustable
OPORA SEDEŽA	Suspension 2-bolt micro-adjustable, 30,9x270mm
SEDEŽ	Selle Royal Look-In gel
PEDALA	Aluminum, VP-183
POGON	
PRESTAVNE ROČICE	Shimano Nexus 8speed Revoshift
ZAVORE	Shimano MT200, hydraulic disc
ZAVORNE ROČICE	Shimano BL-MT201
VERIŽNIK	Gates CDXtm stainless steel 22T rear sprocket
VERIGA	Gates CDXtm Carbon Drive 122T CenterTrack belt
GONILKE Z VERIŽNIKI	Gates CDXtm CenterTrack 46T front sprocket

OBROČNIKI	
OBROČI	Giant eX 2, Tubeless Ready, 700c Aluminium
PESTA	Shimano HB-MT400 100x15mm thru-axle Disc [F], Shimano Nexus 8 Disc brake [R]
NAPERE	Sapim Race [F], Sapim Strong [R]
PLAŠČI	Schwalbe Marathon E Plus 622x50, Smart DualGuard Addix E
DODATNA OPREMA	
SVETILA	Giant Numen iD integrated day-time LED Axa Blueline 30 automatic front LEDAxa Blueline rear LED
PRTLJAŽNIK	MIK rack. System bag & basket compatible

GEOMETRIJA

OKVIR	XS	S	M	L	XL
Dolžina sedežne cevi (mm)	400	450	500	550	600
Kot sedežne cevi	72,5°	72,5°	72,0°	72,0°	72,0°
Top Tube Length (mm)	570	580	595	610	630
Višina glave okvirja (mm)	160	160	170	185	185
Krmlilni kot	69,5°	69,5°	69,5°	69,5°	69,5°
Zamik vpetja osi (mm)	44	44	44	44	44
Trail (mm)	86,9	86,9	86,9	86,9	86,9
Medosna razdalja (mm)	1098	1108	1117	1133	1153
Dolžina cevi ob verigi (mm)	470	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	634	634	643	657	657
Doseg (mm)	370	380	386	396	416
Višina zgornje cevi (mm)	415	407	400	395	855
Širina krmila (mm)	670	670	670	670	670
Dolžina opore krmila (mm)	90	90	90	90	90
Dolžina gonilke (mm)	170	170	170	170	170
Velikost obročnikov	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.