

DAILYTOUR E+ 2 BD LDS

GIANT



SPECS

| HYBRID CYCLING TECHNOLOGY | |
|---------------------------|---|
| MOTOR | SyncDrive Core, 50Nm, Powered by Yamaha |
| CONTROLLER | RideControl Ergo 2 |
| DISPLAY | RideDash Evo |
| BATTERY | EnergyPak Smart 500Wh |
| FRAME | |
| SIZES | XS, S, M, L |
| COLORS | Panther, Indigo |
| FRAME | ALUXX Aluminum |
| FORK | SR Suntour NEX E25, lockout, 63mm , 15AQ |
| COMPONENTS | |
| HANDLEBAR | Giant Contour GT, cable integrated, 30° back sweep 31.8mm |
| GRIPS | Connect Ergo Max Sweep |
| STEM | Giant Contour, EVO display integrated, adjustable |
| SEATPOST | Suspension 2-bolt micro-adjustable, 30,9x270mm |
| SADDLE | Selle Royal Look-In gel |
| PEDALS | Aluminum, VP-183 |
| DRIVETRAIN | |
| SHIFTERS | Shimano Nexus 7speed Revoshift |
| BRAKES | Shimano MT200, hydraulic disc |
| BRAKE LEVERS | Shimano BL-MT201 |
| CASSETTE | Gates CDXtm stainless steel 22T rear sprocket |
| CHAIN | Gates CDXtm Carbon Drive 122T CenterTrack belt |
| CRANKSET | Gates CDXtm CenterTrack 46T front sprocket |

| WHEELS | |
|-----------------|--|
| RIMS | Giant eX 2, Tubeless Ready, 700c Aluminium |
| HUBS | Shimano HB-MT400 100x15mm thru-axle Disc [F], Shimano Nexus 7 Disc brake [R] |
| SPOKES | Sapim Race [F], Sapim Strong [R] |
| TIRES | Schwalbe Marathon 622x50 Green Guard |
| ACCESSORIES | |
| LIGHTING | Axa Blueline 30 front LEDAxa Blueline rear LED |
| CARRIER | MIK rack. System bag & basket compatible |

GEOMETRY

| FRAME | XS | S | M | L | XL |
|--------------------------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 400 | 450 | 500 | 550 | 600 |
| Seat Tube Angle | 72,5° | 72,5° | 72,0° | 72,0° | 72,0° |
| Top Tube Length (mm) | 570 | 580 | 595 | 610 | 630 |
| Head Tube Length (mm) | 160 | 160 | 170 | 185 | 185 |
| Head Tube Angle | 69,5° | 69,5° | 69,5° | 69,5° | 69,5° |
| Fork Rake (mm) | 44 | 44 | 44 | 44 | 44 |
| Trail (mm) | 86,9 | 86,9 | 86,9 | 86,9 | 86,9 |
| Wheelbase (mm) | 1098 | 1108 | 1117 | 1133 | 1153 |
| Chain Stay Length (mm) | 470 | 470 | 470 | 470 | 470 |
| Bottom Bracket Drop (mm) | 60 | 60 | 60 | 60 | 60 |
| Stack (mm) | 634 | 634 | 643 | 657 | 657 |
| Reach (mm) | 370 | 380 | 386 | 396 | 416 |
| Stand Over Height (mm) | 415 | 407 | 400 | 395 | 855 |
| Handlebar Width (mm) | 670 | 670 | 670 | 670 | 670 |
| Stem Length (mm) | 90 | 90 | 90 | 90 | 90 |
| Crank Length (mm) | 170 | 170 | 170 | 170 | 170 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C |

All specifications listed are subject to change without notice.