

DAILYTOUR E+ 2 D LDS

GIANT



SPECS

| HYBRID CYCLING TECHNOLOGY | |
|-----------------------------------|---|
| MOTOR | SyncDrive Sport, 70Nm, Powered by Yamaha |
| SENSOR | RideControl Ergo 2 |
| DISPLAY | RideDash Evo |
| BATTERY | EnergyPak Smart 625Wh |
| CADRU | |
| MARIMI | XS, S, M, L |
| CULORI | Space Grey, Amber Glow |
| CADRU | ALUXX Aluminium |
| FURCA | SR Suntour NEX E25, lockout, 63mm, 15AQ |
| COMPONENTE | |
| GHIDON | Giant Contour GT, cable integrated, 30° back sweep 31.8mm |
| GRIPS | Connect Ergo Max Sweep |
| PIPA | Giant Contour, EVO display integrated, adjustable |
| TIJA SA | Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium |
| SA | Selle Royal Essenza gel |
| PEDALE | Aluminium, VP-183 |
| SISTEMUL DE SCHIMBARE A VITEZELOR | |
| MANETE SCHIMBATOR | Shimano Deore LinkGlide |
| SCHIMBATOR SPATE | Shimano Deore, 10-Speed, LinkGlide, Shadow+ |
| FRANE | Shimano MT200, hydraulic disc |
| MANETE FRANA | Shimano BL-MT201 |
| PINIOANE | Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed |
| LANT | Shimano, LinkGlide, CN-LG500 |
| ANGRENAJ | Giant aluminium, 38T |

| ROTI | |
|-------------|---|
| JANTE | Giant eX25, Tubeless Ready, 700c Aluminium |
| BUTUCI | Giant Tracker Sport [F] 15x100mm Boost [R] 135mm QR |
| SPITE | Sapim Race [F], Sapim Strong [R] |
| ANVELOPE | Schwalbe Energizer Plus, 622x50mm, Green Guard |
| ACCESSORIES | |
| LIGHTING | Axa Blueline 30 front LED Axa Blueline rear LED |
| CARRIER | MIK rack. System bag & basket compatible |

GEOMETRIE

| CADRU | XS | S | M | L | XL |
|--------------------------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 400 | 450 | 500 | 550 | 600 |
| Seat Tube Angle | 72,5° | 72,5° | 72,0° | 72,0° | 72,0° |
| Top Tube Length (mm) | 570 | 580 | 595 | 610 | 630 |
| Head Tube Length (mm) | 160 | 160 | 170 | 185 | 185 |
| Head Tube Angle | 69,5° | 69,5° | 69,5° | 69,5° | 69,5° |
| Fork Rake (mm) | 44 | 44 | 44 | 44 | 44 |
| Trail (mm) | 86,9 | 86,9 | 86,9 | 86,9 | 86,9 |
| Wheelbase (mm) | 1098 | 1108 | 1117 | 1133 | 1153 |
| Chain Stay Length (mm) | 470 | 470 | 470 | 470 | 470 |
| Bottom Bracket Drop (mm) | 60 | 60 | 60 | 60 | 60 |
| Stack (mm) | 634 | 634 | 643 | 657 | 657 |
| Reach (mm) | 370 | 380 | 386 | 396 | 416 |
| Stand Over Height (mm) | 415 | 407 | 400 | 395 | 855 |
| Handlebar Width (mm) | 670 | 670 | 670 | 670 | 670 |
| Stem Length (mm) | 90 | 90 | 90 | 90 | 90 |
| Crank Length (mm) | 170 | 170 | 170 | 170 | 170 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C |

Toate specificatiile enumerate se pot schimba fara notificare prealabila.