

DAILYTOUR E+ 2 D LDS

GIANT



SPECIFIKACIJE

| HIBRIDNA GONILNA TEHNOLOGIJA | |
|------------------------------|---|
| MOTOR | SyncDrive Sport, 70Nm, Powered by Yamaha |
| TIPALO | RideControl Ergo 2 |
| PRIKAZOVALNIK | RideDash Evo |
| BATERIJA | EnergyPak Smart 625Wh |
| OKVIR | |
| VELIKOSTI | XS, S, M, L |
| BARVE | Space Grey, Amber Glow |
| OKVIR | ALUXX Aluminium |
| VILICE | SR Suntour NEX E25, lockout, 63mm, 15AQ |
| KOMPONENTE | |
| KRMILO | Giant Contour GT, cable integrated, 30° back sweep 31.8mm |
| GRIPS | Connect Ergo Max Sweep |
| OPORA KRMILA | Giant Contour, EVO display integrated, adjustable |
| OPORA SEDEŽA | Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium |
| SEDEŽ | Selle Royal Essenza gel |
| PEDALA | Aluminium, VP-183 |
| POGON | |
| PRESTAVNE ROČICE | Shimano Deore LinkGlide |
| ZADNJI MENJALNIK | Shimano Deore, 10-Speed, LinkGlide, Shadow+ |
| ZAVORE | Shimano MT200, hydraulic disc |
| ZAVORNE ROČICE | Shimano BL-MT201 |
| VERIŽNIK | Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed |
| VERIGA | Shimano, LinkGlide, CN-LG500 |
| GONILKE Z VERIŽNIKI | Giant aluminium, 38T |

| OBROČNIKI | |
|----------------|---|
| OBROČI | Giant eX25, Tubeless Ready, 700c Aluminium |
| PESTA | Giant Tracker Sport [F] 15x100mm Boost [R] 135mm QR |
| NAPERE | Sapim Race [F], Sapim Strong [R] |
| PLAŠČI | Schwalbe Energizer Plus, 622x50mm, Green Guard |
| DODATNA OPREMA | |
| SVETILA | Axa Blueline 30 front LED Axa Blueline rear LED |
| PRTLJAŽNIK | MIK rack. System bag & basket compatible |

GEOMETRIJA

| OKVIR | XS | S | M | L | XL |
|--|-------|-------|-------|-------|-------|
| Dolžina sedežne cevi (mm) | 400 | 450 | 500 | 550 | 600 |
| Kot sedežne cevi | 72,5° | 72,5° | 72,0° | 72,0° | 72,0° |
| Top Tube Length (mm) | 570 | 580 | 595 | 610 | 630 |
| Višina glave okvirja (mm) | 160 | 160 | 170 | 185 | 185 |
| Krmljni kot | 69,5° | 69,5° | 69,5° | 69,5° | 69,5° |
| Zamik vpetja osi (mm) | 44 | 44 | 44 | 44 | 44 |
| Trail (mm) | 86,9 | 86,9 | 86,9 | 86,9 | 86,9 |
| Medosna razdalja (mm) | 1098 | 1108 | 1117 | 1133 | 1153 |
| Dolžina cevi ob verigi (mm) | 470 | 470 | 470 | 470 | 470 |
| Bottom Bracket Drop (mm) | 60 | 60 | 60 | 60 | 60 |
| Oddaljenost zgornje cevi od gonilne osi (mm) | 634 | 634 | 643 | 657 | 657 |
| Doseg (mm) | 370 | 380 | 386 | 396 | 416 |
| Višina zgornje cevi (mm) | 415 | 407 | 400 | 395 | 855 |
| Širina krmila (mm) | 670 | 670 | 670 | 670 | 670 |
| Dolžina opore krmila (mm) | 90 | 90 | 90 | 90 | 90 |
| Dolžina gonilke (mm) | 170 | 170 | 170 | 170 | 170 |
| Velikost obročnikov | 700C | 700C | 700C | 700C | 700C |

Vse navedene specifikacije se lahko spremenijo brez obvestila.