



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDrive Core, 50Nm powered by Yamaha
TIPALO	RideControl Dash
PRIKAZOVALNIK	RideControl Dash, full color lcd screen
BATERIJA	EnergyPak Smart 500
OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Panther, Indigo
OKVIR	ALUXX aluminum
VILICE	SR Suntour NEX E25, lockout, 63mm, 15AQ
AMORTIZER	n/a
KOMPONENTE	
KRMILO	Giant Contour GT, cable integrated, 30° back sweep 31.8mm
GRIPS	Connect Ergo Max Sweep
OPORA KRMILA	Giant Contour, EVO display integrated, adjustable
OPORA SEDEŽA	Suspension 2-bolt micro-adjustable, 30,9x270mm
SEDEŽ	Selle Royal Look-In gel
PEDALA	Aluminum, VP-183
POGON	
PRESTAVNE ROČICE	Shimano Nexus 7speed Revoshift
PREDNJI MENJALNIK	-
ZADNJI MENJALNIK	-
ZAVORE	Tektro HD-M285 hydraulic disc
ZAVORNE ROČICE	Tektro HD-M285
VERIŽNIK	Gates CDXtm stainless steel 28T rear sprocket
VERIGA	Gates CDXtm Carbon Drive CenterTrack belt
GONILKE Z VERIŽNIKI	Gates CDXtm CenterTrack 46T front sprocket
BOTTOM BRACKET	n/a

OBROČNIKI	
OBROČI	Giant eX 2, Tubeless Ready, 700c Aluminium
PESTA	Shimano HB-MT400 100x15mm thru-axle Disc [F], Shimano Nexus 7 Disc brake [R]
NAPERE	Sapim Race [F], Sapim Strong [R]
PLAŠČI	Schwalbe Marathon 622x50 Green Guard
DODATNA OPREMA	
SVETILA	Axa Blueline 30 front LED Axa Blueline rear LED
KLJUČAVNICA	Abus Pro Amparo 4750X R
PRTLJAŽNIK	MIK rack. System bag & basket compatible

GEOMETRIJA

OKVIR	S	M	L	XL	XXL
Dolžina sedežne cevi (mm)	450	500	550	600	650
Kot sedežne cevi	72,5°	72,0°	72,0°	72,0°	72,0°
Top Tube Length (mm)	580	590	610	630	645
Višina glave okvirja (mm)	145	160	170	185	200
Krmlini kot	69,5°	69,5°	69,5°	69,5°	69,5°
Zamik vpetja osi (mm)	44	44	44	44	44
Trail (mm)	86,9	86,9	86,9	86,9	86,9
Medosna razdalja (mm)	1107	1112	1132	1153	1153
Dolžina cevi ob verigi (mm)	470	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	620	634	643	657	657
Doseg (mm)	384	384	401	416	416
Višina zgornje cevi (mm)	743	776	818	855	855
Širina krmila (mm)	670	670	670	670	670
Dolžina opore krmila (mm)	90	90	90	90	90
Dolžina gonilke (mm)	170	170	170	170	170
Velikost obročnikov	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.