

DEFY ADVANCED 0

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, M/L, L, XL
FARVER	Ocean Twilight/Chrome
RAMME	Advanced-Grade Composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYR	Giant Contact SL D-Fuse XS:40/42cm, S:40/42cm, M:42/44cm, M/L:42/44cm, L:44/46cm, XL:44/46cm
GREB / STYRBÅND	Stratus Lite 3.0
FREMPIND	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SADELPIND	Giant D-Fuse, composite, 14mm offset
SADEL	Giant Approach
PEDALER	N/A
GEARGRUPPE	
SKIFTEGREB	Shimano 105 Di2
FORSKIFTER	Shimano 105 Di2
BAGSKIFTER	Shimano 105 Di2
BREMSER	Shimano 105 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
BREMSEGREB	Shimano 105 Di2
KASSETTE	Shimano 105, 12-speed, 11x36
KÆDE	KMC X12L-1
KRANKSÆT	Shimano 105, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant SLR 2 36 Carbon Disc WheelSystem
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 3-pawl 30t driver, CenterLock, 12mm thru-axle
EGER	Sapim
DÆK	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EKSTRA	fender mount, water bottle cages, tubeless prepared, 38mm max tire size
GRÆNSER	
MAX DÆKSTØRRELSE	40mm

Pris: 31.999,00 kr.

GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørslængde (mm)	445	480	515	535	565
Sadelrørsvinkel	74,0°	73,5°	73,0°	73,0°	73,0°
Overrørslængde (mm)	530	545	560	575	595
Kronrørslængde (mm)	135	150	175	195	215
Kronrørsvinkel	71,8°	72,5°	72,5°	72,5°	72,5°
Forgaffel fremspring (rake) (mm)	50	50	50	50	50
Sti (mm)	63,4	58,6	58,6	58,6	58,6
Akselafstand (mm)	994	998	1010	1025	1040
Kædestagslængde (mm)	420	420	420	420	420
Krankboks drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Skridthøjde (mm)	733	762	796	814	841
Styrbredde (mm)	400	420	420	440	440
Frempindslængde (mm)	90	100	100	110	110
Pedalarmslængde (mm)	170	172,5	172,5	175	175
Hjulstørrelse	700C	700C	700C	700C	700C

Alle de anførte specifikationer kan ændres uden varsel.