

# DEFY ADVANCED 0



## SPEZIFIKATIONEN

| RAHMEN       |                                                                                                          |
|--------------|----------------------------------------------------------------------------------------------------------|
| GRÖSSEN      | XS, S, M, M/L, L, XL                                                                                     |
| FARBE        | Supernova Grey                                                                                           |
| RAHMEN       | Advanced-grade composite, 12x142mm thru-axle, disc                                                       |
| GABEL        | Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc                     |
| KOMPONENTEN  |                                                                                                          |
| LENKER       | Giant Contact SL D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm |
| GRIFFE       | Stratus Lite 3.0                                                                                         |
| VORBAU       | Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm                           |
| SATTELSTÜTZE | Giant D-Fuse, composite, 14mm offset                                                                     |
| SATTEL       | Giant Approach                                                                                           |
| ANTRIEB      |                                                                                                          |
| SCHALTHEBEL  | Shimano 105 Di2                                                                                          |
| UMWERFER     | Shimano 105 Di2                                                                                          |
| SCHALTWERK   | Shimano 105 Di2                                                                                          |
| BREMSEN      | Shimano 105 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]160mm                                        |
| BREMSHEBEL   | Shimano 105 Di2                                                                                          |
| KASSETTE     | Shimano 105, 12-speed, 11x36                                                                             |
| KETTE        | KMC X12L-1                                                                                               |
| KURBEL       | Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm                          |
| TRETLAGER    | Shimano, press fit                                                                                       |

| LAUFRÄDER          |                                                                                                                |
|--------------------|----------------------------------------------------------------------------------------------------------------|
| FELGEN             | Giant SLR 2 40 Carbon Disc WheelSystem                                                                         |
| NABE               | [F] Giant Alloy Hub, CenterLock, 12mm thru-axle [R] Giant Alloy Hub, 3-pawl driver, CenterLock, 12mm thru-axle |
| SPEICHEN           | Sapim                                                                                                          |
| REIFEN             | Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding                                                       |
| EXTRAS             | tubeless prepared                                                                                              |
| LIMITS             |                                                                                                                |
| MAX TIRE CLEARANCE | 40mm                                                                                                           |

## GEOMETRIEDATEN

| RAHMEN                         | XS    | S     | M     | ML    | L     | XL    |
|--------------------------------|-------|-------|-------|-------|-------|-------|
| Sitzrohrlänge (mm)             | 410   | 445   | 480   | 515   | 535   | 565   |
| Seat Post Insertion Depth (mm) | 190   | 190   | 190   | 190   | 190   | 190   |
| Sitzrohrwinkel                 | 74.5° | 74.0° | 73.5° | 73.0° | 73.0° | 73.0° |
| Oberrohrlänge (mm)             | 515   | 530   | 545   | 560   | 575   | 595   |
| Steuerrohr-Länge (mm)          | 125   | 135   | 150   | 175   | 195   | 215   |
| Steuerrohr-Winkel              | 70.5° | 71.8° | 72.5° | 72.5° | 72.5° | 72.5° |
| Gabelneigung (mm)              | 50    | 50    | 50    | 50    | 50    | 50    |
| Trail (mm)                     | 71.6  | 63.4  | 58.6  | 58.6  | 58.6  | 58.6  |
| Radstand (mm)                  | 995   | 994   | 998   | 1010  | 1025  | 1040  |
| Kettenstreben-Länge (mm)       | 420   | 420   | 420   | 420   | 420   | 420   |
| Tretlager-Höhe (mm)            | 75    | 75    | 75    | 70    | 70    | 70    |
| Stack (mm)                     | 527   | 541   | 558   | 577   | 596   | 615   |
| Reach (mm)                     | 369   | 375   | 380   | 384   | 393   | 402   |
| Überstandshöhe (mm)            | 705   | 733   | 762   | 796   | 814   | 841   |
| Lenkerbreite (mm)              | 410   | 410   | 430   | 430   | 450   | 450   |
| Vorbaulänge (mm)               | 80    | 90    | 100   | 100   | 110   | 110   |
| Kurbellänge (mm)               | 165   | 165   | 170   | 170   | 172.5 | 172.5 |

Spezifikations-, Preis- und Farbänderungen vorbehalten.