

# DEFY ADVANCED 0

GIANT



## SPECS

QUADRO	
TAMANHOS	XS, S, M, M/L, L, XL
CORES	Meteorite Mist
QUADRO	Advanced-grade Composite, 12x142mm thru-axle, disc
FORQUILHA	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTES	
GUIADOR	Giant Contact SL D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
PUNHOS	Stratus Lite 3.0
AVANÇO	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
ESPIGÃO DE SELIM	Giant D-Fuse, composite, 14mm offset
SELIM	Giant Approach
TRANSMISSÃO	
MANETES	Shimano 105 Di2
DESVIADOR DIANTEIRO	Shimano 105 Di2
DESVIADOR TRASEIRO	Shimano 105 Di2
TRAVÕES	Shimano 105 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]160mm
MANÍPULOS DOS TRAVÕES	Shimano 105 Di2
CASSETE	Shimano 105, 12-speed, 11x36
CORRENTE	KMC X12L-1
CONJUNTO PEDALEIRO	Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
MOVIMENTO CENTRAL	Shimano, press fit

RODAS	
AROS	Giant SLR 2 40 Carbon Disc WheelSystem
CUBOS	[F] Giant Alloy Hub, CenterLock, 12mm thru-axle, [R] Giant Alloy Hub, 3-pawl driver, CenterLock, 12mm thru-axle
RAIOS	Sapim
PNEUS	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
EXTRAS	tubeless prepared, 40mm max tire size
LIMITES	
FOLGA MÁXIMA DO PNEU	40mm

Preço: 3 499,00 €

## GEOMETRIA

QUADRO	XS	S	M	ML	L	XL
Comprimento do tubo do assento (mm)	410	445	480	515	535	565
Ângulo do tubo do assento	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Comprimento do tubo superior (mm)	515	530	545	560	575	595
Comprimento do tubo principal (mm)	125	135	150	175	195	215
Ângulo do tubo principal	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Garfo ancinho (mm)	50	50	50	50	50	50
Trilha (mm)	71,6	63,4	58,6	58,6	58,6	58,6
distância entre eixos (mm)	995	994	998	1010	1025	1040
Comprimento Chain Stay (mm)	420	420	420	420	420	420
Suporte inferior (mm)	75	75	75	70	70	70
Pilha (mm)	527	541	558	577	596	615
Alcançar (mm)	369	375	380	384	393	402
Altura do standover (mm)	705	733	762	796	814	841
Largura do guidão (mm)	410	410	430	430	450	450
Comprimento da haste (mm)	80	90	100	100	110	110
Comprimento da Manivela (mm)	165	165	170	170	172,5	172,5

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.