

DEFY ADVANCED 0



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Supernova Grey
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact SL D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
OPORA SEDEŽA	Giant D-Fuse, composite, 14mm offset
SEDEŽ	Giant Approach
POGON	
PRESTAVNE ROČICE	Shimano 105 Di2
PREDNJI MENJALNIK	Shimano 105 Di2
ZADNJI MENJALNIK	Shimano 105 Di2
ZAVORE	Shimano 105 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano 105 Di2
VERIŽNIK	Shimano 105, 12-speed, 11x36
VERIGA	KMC X12L-1
GONILKE Z VERIŽNIKI	Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant SLR 2 40 Carbon Disc WheelSystem
PESTA	[F] Giant Alloy Hub, CenterLock, 12mm thru-axle [R] Giant Alloy Hub, 3-pawl driver, CenterLock, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
DODATKI	tubeless prepared
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	410	445	480	515	535	565
Seat Post Insertion Depth (mm)	190	190	190	190	190	190
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	530	545	560	575	595
Višina glave okvirja (mm)	125	135	150	175	195	215
Krmilni kot	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Zamik vpetja osi (mm)	50	50	50	50	50	50
Trail (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Medosna razdalja (mm)	995	994	998	1010	1025	1040
Dolžina cevi ob verigi (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	527	541	558	577	596	615
Doseg (mm)	369	375	380	384	393	402
Višina zgornje cevi (mm)	705	733	762	796	814	841
Širina krmila (mm)	410	410	430	430	450	450
Dolžina opore krmila (mm)	80	90	100	100	110	110
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.