

DEFY ADVANCED 0



SPECS

RAM	
STORLEKAR	S, M, M/L, L, XL
FÄRGER	Supernova Grey
RAM	Advanced-grade composite, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact SL D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GREPPAR	Stratus Lite 3.0
STAM	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SADELSTOLPE	Giant D-Fuse, composite, 14mm offset
SADEL	Giant Approach
DRIVLINJA	
VÄXLAR	Shimano 105 Di2
FRAMVÄXEL	Shimano 105 Di2
BAKVÄXEL	Shimano 105 Di2
BROMSAR	Shimano 105 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]160mm
BROMSSPAKAR	Shimano 105 Di2
KASSETT	Shimano 105, 12-speed, 11x36
KEDJA	KMC X12L-1
VEVPARTI	Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant SLR 2 40 Carbon Disc WheelSystem
NAV	[F] Giant Alloy Hub, CenterLock, 12mm thru-axle [R] Giant Alloy Hub, 3-pawl driver, CenterLock, 12mm thru-axle
EKRAR	Sapim
DÄCK	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
EXTRAFUNKTIONER	tubeless prepared
GRÄNSER	
MAX DÄCKAVSTÅND	40mm

Price: 48 290,00 kr

GEOMETRY

RAM	S	M	ML	L	XL
Längd sadelrör (mm)	445	480	515	535	565
Vinkel sadelrör	74,0°	73,5°	73,0°	73,0°	73,0°
Topprörets längd (mm)	530	545	560	575	595
Styrhuvud Längd (mm)	135	150	175	195	215
Vinkel styrhuvud	71,8°	72,5°	72,5°	72,5°	72,5°
Gaffelvinkel (mm)	50	50	50	50	50
Spår (mm)	63,4	58,6	58,6	58,6	58,6
Hjulbas (mm)	994	998	1010	1025	1040
Kedjestagslängd (mm)	420	420	420	420	420
Nedre fäste Drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Stå över höjden (mm)	733	762	796	814	841
Styrets bredd (mm)	410	430	430	450	450
Stamlängd (mm)	90	100	100	110	110
Vevlängd (mm)	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.