

DEFY ADVANCED 1

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Charcoal/Milky Way, Black/Helios Orange
CUADRO	Advanced-grade composite, disc
TIJERA	Advanced-grade composite, full-composite steerer, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact SL D-Fuse XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 3.0
POTENCIA	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
POSTE DE ASIENTO	Giant D-Fuse, composite, 14mm offset
ASIENTO	Giant Approach
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano 105 Di2
DESVIADOR	Shimano 105 Di2
CAMBIO TRASERO	Shimano 105 Di2
FRENOS	Shimano 105 Di2 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	Shimano 105 Di2
CASSETTE	Shimano 105, 12-speed, 11x36
CADENA	KMC X12L-1
MULTIPLICACIÓN	Shimano 105, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	Giant P-R2 Disc wheelset, alloy
MAZAS	Giant alloy, 12mm thru-axle
RAYOS	Sapim stainless
NEUMÁTICOS	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRAS	fender mount, water bottle cages, tubeless prepared, 38mm max tire size

Precio: \$78,990.00

GEOMETRÍA

CUADRO	XS	S	M	ML	L
Longitud de la Base del Poste de Asiento (mm)	410	445	480	515	535
Ángulo de la Base del Poste de Asiento	74.5°	74.0°	73.5°	73.0°	73.0°
Longitud del Tubo Superior (mm)	515	530	545	560	575
Longitud del Telescopio (mm)	125	135	150	175	195
Ángulo del Telescopio	70.5°	71.8°	72.5°	72.5°	72.5°
Rake (mm)	50	50	50	50	50
Trail (mm)	71.6	63.4	58.6	58.6	58.6
Distancia entre Ejes (mm)	995	994	998	1010	1025
Longitud de Vaina Inferior (mm)	420	420	420	420	420
Caída del Eje de Centro (mm)	75	75	75	70	70
Stack (mm)	527	541	558	577	596
Reach (mm)	369	375	380	384	393
Altura del Tubo Superior al Suelo (mm)	705	733	762	796	814
Ancho del Manubrio (mm)	400	400	420	420	440
Longitud de la Potencia (mm)	80	90	100	100	110
Longitud de la Biela (mm)	170	170	172.5	172.5	175
Tamaño de las Ruedas	700C	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.