

# DEFY ADVANCED 1



## TEKNISET TIEDOT

| RUNKO          |                                                                                              |
|----------------|----------------------------------------------------------------------------------------------|
| KOOT           | XS, S, M, M/L, L, XL                                                                         |
| VÄRIT          | Frost Silver/Cordovan, Solar Flare                                                           |
| RUNKO          | Advanced-Grade Composite, 12x142mm thru-axle, disc                                           |
| HAARUKKA       | Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc         |
| KOMONENTIT     |                                                                                              |
| OHJAUSTANKO    | Giant Contact SL D-Fuse XS:40/42cm, S:40/42cm, M:42/44cm, M/L:42/44cm, L:44/46cm, XL:44/46cm |
| GRIPIT         | Stratus Lite 3.0                                                                             |
| OHJAINKANNATIN | Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm               |
| SATULATOLPPA   | Giant D-Fuse, composite, 14mm offset                                                         |
| SATULA         | Giant Approach                                                                               |
| POLKIMET       | N/A                                                                                          |
| VOIMANSIIRTO   |                                                                                              |
| VAIHDEVIPU     | Shimano 105 Di2                                                                              |
| ETUVAIHTAJA    | Shimano 105 Di2                                                                              |
| TAKAVAIHTAJA   | Shimano 105 Di2                                                                              |
| JARRUT         | Shimano 105 Di2 hydraulic, Giant MPH rotors [F]160mm, [R]160mm                               |
| JARRUKAHVAT    | Shimano 105 Di2                                                                              |
| RATASPAKKA     | Shimano 105, 12-speed, 11x36                                                                 |
| KETJUT         | KMC X12L-1                                                                                   |
| KAMPISARJA     | Shimano 105, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm              |
| KESKIÖ         | Shimano, press fit                                                                           |

| RENKAAT        |                                                                         |
|----------------|-------------------------------------------------------------------------|
| VANTEET        | Giant P-R2 Disc wheelset, alloy, [F]25mm, [R]25mm                       |
| NAVAT          | Giant alloy, 12mm thru-axle                                             |
| PINNAT         | Sapim                                                                   |
| RENKAAT        | Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding                |
| LISÄTIEDOT     | fender mount, water bottle cages, tubeless prepared, 38mm max tire size |
| RAJOITTEET     |                                                                         |
| MAX RENGASVARA | 40mm                                                                    |

Suositusinta: 3 729,00 €

## GEOMETRIA

| RUNKO                              | S     | M     | ML    | L     | XL    |
|------------------------------------|-------|-------|-------|-------|-------|
| Satulaputken pituus (mm)           | 445   | 480   | 515   | 535   | 565   |
| Satulaputken kulma                 | 74,0° | 73,5° | 73,0° | 73,0° | 73,0° |
| Vaakaputken pituus (mm)            | 530   | 545   | 560   | 575   | 595   |
| Emäputken pituus (mm)              | 135   | 150   | 175   | 195   | 215   |
| Emäputken kulma                    | 71,8° | 72,5° | 72,5° | 72,5° | 72,5° |
| Haarukan offset (mm)               | 50    | 50    | 50    | 50    | 50    |
| Trail-mitta (mm)                   | 63,4  | 58,6  | 58,6  | 58,6  | 58,6  |
| Akseliväli (mm)                    | 994   | 998   | 1010  | 1025  | 1040  |
| Takahaarukan alaputken pituus (mm) | 420   | 420   | 420   | 420   | 420   |
| Keskiön pudotus (mm)               | 75    | 75    | 70    | 70    | 70    |
| Stack-mitta (mm)                   | 541   | 558   | 577   | 596   | 615   |
| Reach-mitta (mm)                   | 375   | 380   | 384   | 393   | 402   |
| Standover-mitta (mm)               | 733   | 762   | 796   | 814   | 841   |
| Ohjaustangon leveys (mm)           | 400   | 420   | 420   | 440   | 440   |
| Ohjainkannattimen pituus (mm)      | 90    | 100   | 100   | 110   | 110   |
| Kammen pituus (mm)                 | 170   | 172,5 | 172,5 | 175   | 175   |
| Rengaskoko                         | 700C  | 700C  | 700C  | 700C  | 700C  |

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.