

DEFY ADVANCED 2

GIANT



SPEZIFIKATIONEN

RAHMEN & GABEL	
RAHMENGRÖSSEN	XS, S, M, M/L, L, XL
FARBE(N)	Pearl White, Tidal Green
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, disc
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COCKPIT	
LENKER	Giant Contact SL D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIFFE	Stratus Lite 3.0
VORBAU	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SATTELSTÜTZE	Giant D-Fuse, composite, 14mm offset
SATTEL	Giant Approach
SCHALTUNG, ANTRIEB	
SCHALTHEBEL	Shimano 105
UMWERFER	Shimano 105
SCHALTWERK	Shimano 105
BREMSEN	Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors [F]160mm, [R]160mm
BREMSEHEBEL	Shimano 105
KASSETTE	Shimano 105, 11x36
KETTE	KMC X12L-1
KURBELSATZ	Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
INNENLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant P-R1 Disc wheelset, alloy, [F]25mm, [R]25mm
NABEN (V/H)	Giant alloy, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
ZUBEHÖR (TEILW. VERBAUT)	Tubeless Prepared
GRENZEN	
MAX. REIFENBREITE	40mm

UVP: 2.700,00 €

GEOMETRIEDATEN

RAHMEN & GABEL	S	M	ML	L	XL
Sitzrohrlänge (mm)	445	480	515	535	565
Einstecktiefe der Sattelstütze (mm)	190	190	190	190	190
Sitzwinkel	74,0°	73,5°	73,0°	73,0°	73,0°
Oberrohrlänge (mm)	530	545	560	575	595
Steuerrohrlänge (mm)	135	150	175	195	215
Lenkwinkel	71,8°	72,5°	72,5°	72,5°	72,5°
Gabelvorbiegung (mm)	50	50	50	50	50
Gabelnachlauf (mm)	63,4	58,6	58,6	58,6	58,6
Radstand (mm)	994	998	1010	1025	1040
Kettenstrebenlänge (mm)	420	420	420	420	420
Tretlagerabsenkung (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Überstands-/Durchstiegshöhe (mm)	733	762	796	814	841
Lenkerbreite (mm)	410	430	430	450	450
Vorbaulänge (mm)	90	100	100	110	110
Kurbelarmlänge (mm)	165	170	170	172,5	172,5

Spezifikations-, Preis- und Farbänderungen vorbehalten.