



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Mars Dust, Carbon
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SL D-Fuse XS:40/42cm, S:40/42cm, M:42/44cm, M/L:42/44cm, L:44/46cm, XL:44/46cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SEATPOST	Giant D-Fuse, composite, 14mm offset
SADDLE	Giant Approach
DRIVETRAIN	
SHIFTERS	Shimano 105
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
BRAKES	Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano 105
CASSETTE	Shimano 105, 11x36
CHAIN	KMC X12L-1
CRANKSET	Shimano FC-RS520, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant P-R2 Disc wheelset, alloy, [F]25mm, [R]25mm
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRAS	fender mount, water bottle cages, tubeless prepared, 38mm max tire size

Recommended Retail Price: \$3,300.00

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (inch)	16.1	17.5	18.9	20.3	21.1	22.2
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (inch)	20.3	20.9	21.5	22	22.6	23.4
Head Tube Length (inch)	4.7	5.5	5.9	6.9	7.7	8.5
Head Tube Angle	70.5°	71.8°	72.5°	72.5°	72.5°	72.5°
Fork Rake (inch)	2	2	2	2	2	2
Trail (inch)	2.8	2.5	2.3	2.3	2.3	2.3
Wheelbase (inch)	39.2	39.1	39.3	39.8	40.4	40.9
Chain Stay Length (inch)	16.5	16.5	16.5	16.5	16.5	16.5
Bottom Bracket Drop (inch)	3	3	3	2.8	2.8	2.8
Stack (inch)	20.7	21.3	22	22.7	23.5	24.2
Reach (inch)	14.5	14.8	15	15.1	15.5	15.8
Stand Over Height (inch)	27.8	28.9	30	31.3	32	33.1
Handlebar Width (inch)	15.7	15.7	16.5	16.5	17.3	17.3
Stem Length (inch)	3.1	3.5	3.9	3.9	4.3	4.3
Crank Length (inch)	6.7	6.7	6.8	6.8	6.9	6.9
Wheel Size	700C	700C	700C	700C	700C	700C

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*