

DEFY ADVANCED 2

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Pearl White, Tidal Green
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SL D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SEATPOST	Giant D-Fuse, composite, 14mm offset
SADDLE	Giant Approach
DRIVETRAIN	
SHIFTERS	Shimano 105
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
BRAKES	Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano 105
CASSETTE	Shimano 105, 11x36
CHAIN	KMC X12L-1
CRANKSET	Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant P-R1 Disc wheelset, alloy, [F]25mm, [R]25mm
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRAS	Tubeless Prepared
LIMITS	
MAX TIRE CLEARANCE	40mm

Recommended Retail Price: \$3,300.00

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (inch)	16.1	17.5	18.9	20.3	21.1	22.2
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (inch)	20.3	20.9	21.5	22	22.6	23.4
Head Tube Length (inch)	4.9	5.3	5.9	6.9	7.7	8.5
Head Tube Angle	70.5°	71.8°	72.5°	72.5°	72.5°	72.5°
Fork Rake (inch)	2	2	2	2	2	2
Trail (inch)	2.8	2.5	2.3	2.3	2.3	2.3
Wheelbase (inch)	39.2	39.1	39.3	39.8	40.4	40.9
Chain Stay Length (inch)	16.5	16.5	16.5	16.5	16.5	16.5
Bottom Bracket Drop (inch)	3	3	3	2.8	2.8	2.8
Stack (inch)	20.7	21.3	22	22.7	23.5	24.2
Reach (inch)	14.5	14.8	15	15.1	15.5	15.8
Stand Over Height (inch)	27.8	28.9	30	31.3	32	33.1
Handlebar Width (inch)	16.1	16.1	16.9	16.9	17.7	17.7
Stem Length (inch)	3.1	3.5	3.9	3.9	4.3	4.3
Crank Length (inch)	6.5	6.5	6.7	6.7	6.8	6.8

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*