

DEFY ADVANCED 2



TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Bay Leaf/Early Espresso
CADRE	Advanced-grade composite, disc
FOURCHE	Advanced-grade composite, full-composite steerer, disc
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Contact SL D-Fuse XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
POIGNÉES	Stratus Lite 3.0
POTENCE	Giant Contact Aero Light XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
TIGE DE SELLE	Giant D-Fuse, composite, 14mm offset
SELLE	Giant Approach
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	Shimano 105
DÉRAILLEUR AVANT	Shimano 105
DÉRAILLEUR ARRIÈRE	Shimano 105
FREINS	Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
LEVIER DE FREIN	Shimano 105
CASSETTE	Shimano 105, 11x36
CHAÎNE	KMC X12L-1
PÉDALIER	Shimano FC-RS520, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOITIER DE PÉDALIER	Shimano, press fit RS500

ROUES	
JANTES	Giant P-R2 Disc wheelset, alloy
MOYEUX	Giant alloy, 12mm thru-axle
RAYONS	Sapim stainless
PNEUS	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRAS	fender mount, water bottle cages, tubeless prepared, 38mm max tire size
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 3 000,00 €

GÉOMÉTRIE

CADRE	XS	S	M	ML	L	XL
Longueur de tube de selle (mm)	410	445	480	515	535	565
Angle de tube de selle	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Longueur du tube supérieur (mm)	515	530	545	560	575	595
Longueur du tube de direction (mm)	125	135	150	175	195	215
Angle du tube de direction	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Déport de fourche (mm)	50	50	50	50	50	50
Trail (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Empattement (mm)	995	994	998	1010	1025	1040
Longueur des bases (mm)	420	420	420	420	420	420
Drop du boîtier de pédalier (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Hauteur en statique (mm)	705	733	762	796	814	841
Largeur de cintre (mm)	400	400	420	420	440	440
Longueur de potence (mm)	80	90	100	100	110	110
Longueur des manivelles (mm)	170	170	172,5	172,5	175	175
Diamètre des roues	700C	700C	700C	700C	700C	700C

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.