

DEFY ADVANCED 2

GIANT



TECHNIQUES

CADRE	
TAILLES	XS, S, M, ML, L, XL
COLORIS	Pearl White
CADRE	Advanced-grade composite, 12x142mm thru-axle, disc
FOURCHE	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPOSANTS	
CINTRE	Giant Contact SL D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
POIGNÉES	Stratus Lite 3.0
POTENCE	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
TIGE DE SELLE	Giant D-Fuse, composite, 14mm offset
SELLE	Giant Approach
DÉRAILLEUR	
MANETTES	Shimano 105
DÉRAILLEUR AVANT	Shimano 105
DÉRAILLEUR ARRIÈRE	Shimano 105
FREINS	Shimano 105 hydraulic, Shimano SM-RT64 rotors [F]160mm, [R]160mm
LEVIERS DE FREIN	Shimano 105
CASSETTE	Shimano 105, 11x36
CHAÎNE	KMC X12L-1
PÉDALIER	Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOITIER DE PÉDALIER	Shimano, press fit

ROUES	
JANTES	Giant P-R1 Disc wheelset, alloy, [F]25mm, [R]25mm
MOYEURS	Giant alloy, 12mm thru-axle
RAYONS	Sapim
PNEUS	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRAS	Tubeless Prepared
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
DÉGAGEMENT MAX DES PNEUS	40mm

Prix Public Conseillé: 2 600,00 €

GÉOMÉTRIE

CADRE	XS	S	M	ML	L	XL
Longueur de tube de selle (mm)	410	445	480	515	535	565
Angle de tube de selle	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Longueur du tube supérieur (mm)	515	530	545	560	575	595
Longueur du tube de direction (mm)	125	135	150	175	195	215
Angle du tube de direction	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Déport de fourche (mm)	50	50	50	50	50	50
Trail (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Empattement (mm)	995	994	998	1010	1025	1040
Longueur des bases (mm)	420	420	420	420	420	420
Drop du boîtier de pédalier (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Hauteur en statique (mm)	705	733	762	796	814	841
Largeur de cintre (mm)	410	410	430	430	450	450
Longueur de potence (mm)	80	90	100	100	110	110
Longueur des manivelles (mm)	165	165	170	170	172,5	172,5

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.