

DEFY ADVANCED 3

GIANT



SPEZIFIKATIONEN

| RAHMEN & GABEL     |                                                                                                          |
|--------------------|----------------------------------------------------------------------------------------------------------|
| RAHMENGRÖSSEN      | XS, S, M, M/L, L, XL                                                                                     |
| FARBE(N)           | Mach Blue                                                                                                |
| RAHMEN             | Advanced-grade composite, 12x142mm thru-axle, disc                                                       |
| GABEL              | Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc                     |
| COCKPIT            |                                                                                                          |
| LENKER             | Giant Contact SL D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm |
| GRIFFE             | Stratus Lite 3.0                                                                                         |
| VORBAU             | Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm                           |
| SATTELSTÜTZE       | Giant D-Fuse, composite, 14mm offset                                                                     |
| SATTEL             | Giant Approach                                                                                           |
| SCHALTUNG, ANTRIEB |                                                                                                          |
| SCHALTHEBEL        | Shimano Tiagra R4000                                                                                     |
| UMWERFER           | Shimano Tiagra R4000                                                                                     |
| SCHALTWERK         | Shimano Tiagra R4000                                                                                     |
| BREMSEN            | Shimano BR-RS405 hydraulic, Giant MPH rotors [F]160mm, [R]160mm                                          |
| BREMSEHEBEL        | Shimano Tiagra R4000                                                                                     |
| KASSETTE           | Shimano CS-RS400, 11-speed, 11x36                                                                        |
| KETTE              | KMC X11                                                                                                  |
| KURBELSATZ         | Shimano FC-R4000, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm                     |
| INNENLAGER         | Shimano, press fit                                                                                       |

| LAUFRÄDER                |                                                          |
|--------------------------|----------------------------------------------------------|
| FELGEN                   | Giant S-R2 Disc wheelset, alloy, [F]25mm, [R]25mm        |
| NABEN (V/H)              | Giant alloy, 12mm thru-axle                              |
| SPEICHEN                 | Sapim                                                    |
| REIFEN                   | Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding |
| ZUBEHÖR (TEILW. VERBAUT) | Tubeless Prepared                                        |
| GRENZEN                  |                                                          |
| MAX. REIFENBREITE        | 40mm                                                     |

UVP: 2.300,00 €

GEOMETRIEDATEN

| RAHMEN & GABEL                      | S     | M     | ML    | L     | XL    |
|-------------------------------------|-------|-------|-------|-------|-------|
| Sitzrohrlänge (mm)                  | 445   | 480   | 515   | 535   | 565   |
| Einstecktiefe der Sattelstütze (mm) | 190   | 190   | 190   | 190   | 190   |
| Sitzwinkel                          | 74,0° | 73,5° | 73,0° | 73,0° | 73,0° |
| Oberrohrlänge (mm)                  | 530   | 545   | 560   | 575   | 595   |
| Steuerrohrlänge (mm)                | 135   | 150   | 175   | 195   | 215   |
| Lenkwinkel                          | 71,8° | 72,5° | 72,5° | 72,5° | 72,5° |
| Gabelvorbiegung (mm)                | 50    | 50    | 50    | 50    | 50    |
| Gabelnachlauf (mm)                  | 63,4  | 58,6  | 58,6  | 58,6  | 58,6  |
| Radstand (mm)                       | 994   | 998   | 1010  | 1025  | 1040  |
| Kettenstrebenlänge (mm)             | 420   | 420   | 420   | 420   | 420   |
| Tretlagerabsenkung (mm)             | 75    | 75    | 70    | 70    | 70    |
| Stack (mm)                          | 541   | 558   | 577   | 596   | 615   |
| Reach (mm)                          | 375   | 380   | 384   | 393   | 402   |
| Überstands-/Durchstiegshöhe (mm)    | 733   | 762   | 796   | 814   | 841   |
| Lenkerbreite (mm)                   | 410   | 430   | 430   | 450   | 450   |
| Vorbaulänge (mm)                    | 90    | 100   | 100   | 110   | 110   |
| Kurbelarmlänge (mm)                 | 165   | 170   | 170   | 172,5 | 172,5 |

Spezifikations-, Preis- und Farbänderungen vorbehalten.