

DEFY ADVANCED 3

GIANT



SPECS

| FRAME            |                                                                                                          |
|------------------|----------------------------------------------------------------------------------------------------------|
| SIZES            | XS, S, M, M/L, L, XL                                                                                     |
| COLOURS          | Mach Blue                                                                                                |
| FRAME            | Advanced-grade composite, 12x142mm thru-axle, disc                                                       |
| FORK             | Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc                     |
| COMPONENTS       |                                                                                                          |
| HANDLEBAR        | Giant Contact SL D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm |
| GRIPS            | Stratus Lite 3.0                                                                                         |
| STEM             | Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm                           |
| SEATPOST         | Giant D-Fuse, composite, 14mm offset                                                                     |
| SADDLE           | Giant Approach                                                                                           |
| DRIVETRAIN       |                                                                                                          |
| SHIFTERS         | Shimano Tiagra R4000                                                                                     |
| FRONT DERAILLEUR | Shimano Tiagra R4000                                                                                     |
| REAR DERAILLEUR  | Shimano Tiagra R4000                                                                                     |
| BRAKES           | Shimano BR-RS405 hydraulic, Giant MPH rotors [F]160mm, [R]160mm                                          |
| BRAKE LEVERS     | Shimano Tiagra R4000                                                                                     |
| CASSETTE         | Shimano CS-RS400, 11-speed, 11x36                                                                        |
| CHAIN            | KMC X11                                                                                                  |
| CRANKSET         | Shimano FC-R4000, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm                     |
| BOTTOM BRACKET   | Shimano, press fit                                                                                       |

| WHEELS             |                                                          |
|--------------------|----------------------------------------------------------|
| RIMS               | Giant S-R2 Disc wheelset, alloy, [F]25mm, [R]25mm        |
| HUBS               | Giant alloy, 12mm thru-axle                              |
| SPOKES             | Sapim                                                    |
| TYRES              | Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding |
| EXTRAS             | Tubeless Prepared                                        |
| LIMITS             |                                                          |
| MAX TIRE CLEARANCE | 40mm                                                     |

Price: €2,399.00

GEOMETRY

| FRAME                          | XS    | S     | M     | ML    | L     | XL    |
|--------------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm)          | 410   | 445   | 480   | 515   | 535   | 565   |
| Seat Post Insertion Depth (mm) | 190   | 190   | 190   | 190   | 190   | 190   |
| Seat Tube Angle                | 74.5° | 74.0° | 73.5° | 73.0° | 73.0° | 73.0° |
| Top Tube Length (mm)           | 515   | 530   | 545   | 560   | 575   | 595   |
| Head Tube Length (mm)          | 125   | 135   | 150   | 175   | 195   | 215   |
| Head Tube Angle                | 70.5° | 71.8° | 72.5° | 72.5° | 72.5° | 72.5° |
| Fork Rake (mm)                 | 50    | 50    | 50    | 50    | 50    | 50    |
| Trail (mm)                     | 71.6  | 63.4  | 58.6  | 58.6  | 58.6  | 58.6  |
| Wheelbase (mm)                 | 995   | 994   | 998   | 1010  | 1025  | 1040  |
| Chain Stay Length (mm)         | 420   | 420   | 420   | 420   | 420   | 420   |
| Bottom Bracket Drop (mm)       | 75    | 75    | 75    | 70    | 70    | 70    |
| Stack (mm)                     | 527   | 541   | 558   | 577   | 596   | 615   |
| Reach (mm)                     | 369   | 375   | 380   | 384   | 393   | 402   |
| Stand Over Height (mm)         | 705   | 733   | 762   | 796   | 814   | 841   |
| Handlebar Width (mm)           | 410   | 410   | 430   | 430   | 450   | 450   |
| Stem Length (mm)               | 80    | 90    | 100   | 100   | 110   | 110   |
| Crank Length (mm)              | 165   | 165   | 170   | 170   | 172.5 | 172.5 |

All specifications listed are subject to change without notice.