

DEFY ADVANCED E+ ELITE 0



СПЕЦИФИКАЦИИ

ХИБРИДНА ТЕХНОЛОГИЯ ЗА КОЛОЕЗДЕНЕ	
МОТОР	SyncDriveMove Plus Hub drive 75Nm max
КОНТРОЛЕР	Mode support switch from SRAM bonus button
ДИСПЛЕЙ	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
БАТЕРИЯ	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
ЗАРЯДНО	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
РАМКА	
РАЗМЕР	S, M, ML, L, XL
ЦВЯТ	Blue Dragonfly / Black
РАМКА	Advanced-grade composite,12x145 thru-axle
ВИЛКА	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
ЗАДЕН АМОРТИСЬОР	-
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact SLR D-Fuse 31.8 carbon
ЛАПА	Contact SLR Aerolight 31.8 carbon
КОЛЧЕ ЗА СЕДАЛКА	Giant D-Fuse SLR, Composite, -5/+15mm offset
СЕДАЛКА	Giant Fleet SL
DRIVETRAIN	
КОМАНДИ	Sram RED AXS
ПРЕДЕН ДЕРАЙЛЪОР	Sram RED AXS
ЗАДЕН ДЕРАЙЛЪОР	Sram RED AXS
СПИРАЧКИ	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
РЪКОХВАТКИ ЗА СПИРАЧКИ	Sram RED AXS HRD
КАСЕТА	SRAM RED XG-1290 10x33T 12-speed
ВЕРИГА	Sram RED 12-speed
КУРБЕЛ	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
СРЕДНА КАСЕТА	Giant E+ System BBSS

КАПЛИ	
ШИНИ	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle
СПИЦИ	Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
ГУМИ	Cadex Classic 95PSI 700x28C 170TPI Tubeless Foldable
АКСЕСОАРИ	
СВЕТЛИНИ	Seatpost clamp integrated tail light

ГЕОМЕТРИЯ

РАМКА	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	530	545	560	575	590
Head Tube Length (mm)	130	145	167	187	205
Head Tube Angle	71,5°	72,5°	72,5°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	65,1	58,6	58,6	58,6	58,6
Wheelbase (mm)	994,3	995,2	1007,5	1022,7	1037,9
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542,2	560,2	576,1	595,2	612,4
Обсер (mm)	374,3	378,9	383,6	392,8	402,6
Stand Over Height (mm)	716	745,5	779	799	824
Ширина на Кормило (mm)	400	420	420	440	440
Дължина на Лапа (mm)	90	100	110	110	120
Дължина на Курбел (mm)	170	172,5	172,5	175	175
Размер на Каплите	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.