

DEFY ADVANCED E+ ELITE 0

GIANT



SPECIFIKATIONER

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
KONTROLLER	Mode support switch from SRAM bonus button
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERI	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADER	Giant EnergyPak smart charger 4A
FORBINDELSE	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RAMME	
STØRRELSER	S, M, ML, L, XL
FARVER	Midnight Moon
RAMME	Advanced-grade composite, 12x145 thru-axle
FORGAFFEL	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
BAGDÆMPER	-
KOMPONENTER	
STYR	Giant Contact SLR D-Fuse 31.8 carbon
FREMPIND	Contact SLR Aerolight 31.8 carbon
SADELPIND	Giant D-Fuse SLR, Composite, -5/+15mm offset
SADEL	Giant Fleet SL
GEARGRUPPE	
SKIFTEGREB	Sram RED AXS
FORSKIFTER	Sram RED AXS
BAGSKIFTER	Sram RED AXS
BREMSE	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
BREMSEGREB	Sram RED AXS HRD
KASSETTE	SRAM RED XG-1290 10x33T 12-speed
KÆDE	Sram RED 12-speed
KRANKSÆT	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
KRANKBOKS	Giant E+ System BBSS

HJUL	
FÆLGE	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
DÆK	Cadex Race GC, tubeless, 700x30, folding
EKSTRA	Fender adapter
TILBEHØR	
LYGTER	Seatpost clamp integrated tail light

Pris: **82.999,00 kr.**

GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørlængde (mm)	445	480	515	535	565
Sadelrørsinkel	74,0°	73,5°	73,0°	73,0°	73,0°
Overrørlængde (mm)	530	545	560	575	590
Kronrørlængde (mm)	130	145	167	187	205
Kronrørsinkel	71,5°	72,5°	72,5°	72,5°	72,5°
Forgaffel fremspring (rake) (mm)	50	50	50	50	50
Sti (mm)	56,1	58,6	58,6	58,6	58,6
Akselafstand (mm)	994	995	1008	1023	1037,9
Kædestagslængde (mm)	420	420	420	420	420
Krankboks drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Skridthøjde (mm)	716	746	779	799	824
Styrbredde (mm)	400	420	420	440	440
Frempindslængde (mm)	90	100	110	110	120
Hjulstørrelse	700C	700C	700C	700C	700C

Alle de anførte specifikationer kan ændres uden varsel.