

DEFY ADVANCED E+ ELITE 0

GIANT



SPECS

| HYBRID CYCLING TECHNOLOGY | |
|---------------------------|--|
| MOTOR | SyncDriveMove Plus Hub drive 75Nm max |
| CONTROLLER | Mode support switch from SRAM bonus button |
| DISPLAY | Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display |
| BATTERY | Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible |
| CHARGER | Giant EnergyPak smart charger 4A |
| CONNECTIVITY | Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile |
| ΣΚΕΛΕΤΟΣ | |
| ΜΕΓΕΘΗ | S, M, ML, L, XL |
| ΧΡΩΜΑΤΑ | Midnight Moon |
| ΣΚΕΛΕΤΟΣ | Advanced-grade composite, 12x145 thru-axle |
| ΠΙΡΟΥΝΙ | Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc |
| ΑΝΑΡΤΗΣΗ | - |
| ΕΞΑΡΤΗΜΑΤΑ | |
| ΤΙΜΟΝΙ | Giant Contact SLR D-Fuse 31.8 carbon |
| ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ | Contact SLR Aerolight 31.8 carbon |
| ΛΑΙΜΟΣ ΣΕΛΛΑΣ | Giant D-Fuse SLR, Composite, -5/+15mm offset |
| ΣΕΛΛΑ | Giant Fleet SL |
| ΜΕΤΑΔΟΣΗ | |
| ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ | Sram RED AXS |
| ΝΤΕΡΑΓΙΕΡ ΕΜΠΡΟΣΘΙΟ | Sram RED AXS |
| ΝΤΕΡΑΓΙΕΡ ΟΠΙΣΘΙΟ. | Sram RED AXS |
| ΦΡΕΝΑ | Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R] |
| ΜΑΝΥΕΤΕΣ ΦΡΕΝΩΝ | Sram RED AXS HRD |
| CASETTE Ή ΕΛΕΥΘΕΡΟ | SRAM RED XG-1290 10x33T 12-speed |
| ΑΛΥΣΙΔΑ | Sram RED 12-speed |
| ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ | Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS |
| ΒΟΤΤΟΜ BRACKET | Giant E+ System BBSS |

| WHEELS | |
|-------------|---|
| ΣΤΕΦΑΝΙΑ | Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized |
| ΕΛΑΣΤΙΚΑ | Cadex Race GC, tubeless, 700x30, folding |
| EXTRAS | Fender adapter |
| ACCESSORIES | |
| LIGHTING | Seatpost clamp integrated tail light |

ΓΕΩΜΕΤΡΙΑ

| ΣΚΕΛΕΤΟΣ | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|--------|
| Seat Tube Length (mm) | 445 | 480 | 515 | 535 | 565 |
| Seat Tube Angle | 74,0° | 73,5° | 73,0° | 73,0° | 73,0° |
| Top Tube Length (mm) | 530 | 545 | 560 | 575 | 590 |
| Head Tube Length (mm) | 130 | 145 | 167 | 187 | 205 |
| Head Tube Angle | 71,5° | 72,5° | 72,5° | 72,5° | 72,5° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | 50 |
| Trail (mm) | 56,1 | 58,6 | 58,6 | 58,6 | 58,6 |
| Wheelbase (mm) | 994 | 995 | 1008 | 1023 | 1037,9 |
| Chain Stay Length (mm) | 420 | 420 | 420 | 420 | 420 |
| Bottom Bracket Drop (mm) | 80 | 80 | 75 | 75 | 75 |
| Stack (mm) | 542 | 560 | 576 | 595 | 612,4 |
| Reach (mm) | 374 | 379 | 384 | 393 | 402,6 |
| Stand Over Height (mm) | 716 | 746 | 779 | 799 | 824 |
| Handlebar Width (mm) | 400 | 420 | 420 | 440 | 440 |
| Stem Length (mm) | 90 | 100 | 110 | 110 | 120 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C |

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση