

DEFY ADVANCED E+ ELITE 0

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
CONTROLLER	Mode support switch from SRAM bonus button
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, ML, L, XL
COLORS	Midnight Moon
FRAME	Advanced-grade composite, 12x145 thru-axle
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
SHOCK	-
COMPONENTS	
HANDLEBAR	Giant Contact SLR D-Fuse 31.8 carbon
STEM	Contact SLR Aerolight 31.8 carbon
SEATPOST	Giant D-Fuse SLR, Composite, -5/+15mm offset
SADDLE	Giant Fleet SL
DRIVETRAIN	
SHIFTERS	Sram RED AXS
FRONT DERAILLEUR	Sram RED AXS
REAR DERAILLEUR	Sram RED AXS
BRAKES	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
BRAKE LEVERS	Sram RED AXS HRD
CASSETTE	SRAM RED XG-1290 10x33T 12-speed
CHAIN	Sram RED 12-speed
CRANKSET	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS	
RIMS	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
TIRES	Cadex Race GC, tubeless, 700x30, folding
EXTRAS	Fender adapter
ACCESSORIES	
LIGHTING	Seatpost clamp integrated tail light

Recommended Retail Price: \$12,000.00

GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (inch)	17.5	18.9	20.3	21.1	22.2
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (inch)	20.9	21.5	22	22.6	23.2
Head Tube Length (inch)	5.1	5.7	6.6	7.4	8.1
Head Tube Angle	71.5°	72.5°	72.5°	72.5°	72.5°
Fork Rake (inch)	2	2	2	2	2
Trail (inch)	2.2	2.3	2.3	2.3	2.3
Wheelbase (inch)	39.1	39.2	39.7	40.3	40.8
Chain Stay Length (inch)	16.5	16.5	16.5	16.5	16.5
Bottom Bracket Drop (inch)	3.1	3.1	3	3	3
Stack (inch)	21.3	22	22.7	23.4	24.1
Reach (inch)	14.7	14.9	15.1	15.5	15.8
Stand Over Height (inch)	28.2	29.4	30.7	31.5	32.4
Handlebar Width (inch)	15.7	16.5	16.5	17.3	17.3
Stem Length (inch)	3.5	3.9	4.3	4.3	4.7
Wheel Size	700C	700C	700C	700C	700C

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*