

DEFY ADVANCED E+ ELITE 0

GIANT



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	SyncDriveMove Plus Hub drive 75Nm max
OHJAUSYKSIKKÖ	Mode support switch from SRAM bonus button
NÄYTTÖ	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
AKKU	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LATURI	Giant EnergyPak smart charger 4A
YHTEYDET MUIHIN LAITTEISIIN	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RUNKO	
KOOT	S, M, ML, L, XL
VÄRIT	Midnight Moon
RUNKO	Advanced-grade composite, 12x145 thru-axle
HAARUKKA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
ISKUNVAIMENNIN	-
KOMPONENTIT	
OHJAUSTANKKO	Giant Contact SLR D-Fuse 31.8 carbon
OHJAINKANNATIN	Contact SLR Aerolight 31.8 carbon
SATULATOLPPA	Giant D-Fuse SLR, Composite, -5/+15mm offset
SATULA	Giant Fleet SL
VOIMANSIIRTO	
VAIHDEVIPU	Sram RED AXS
ETUVAIHTAJA	Sram RED AXS
TAKAVAIHTAJA	Sram RED AXS
JARRUT	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
JARRUKAHVAT	Sram RED AXS HRD
RATASPAKKA	SRAM RED XG-1290 10x33T 12-speed
KETJUT	Sram RED 12-speed
KAMPISARJA	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
KESKIÖ	Giant E+ System BBSS

RENKAAT	
VANTEET	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
RENKAAT	Cadex Race GC, tubeless, 700x30, folding
LISÄTIEDOT	Fender adapter
TARVIKKEET	
VALOT	Seatpost clamp integrated tail light

Suositusuhinta: 11 199,00 €

GEOMETRIA

RUNKO	S	M	ML	L	XL
Satulaputken pituus (mm)	445	480	515	535	565
Satulaputken kulma	74,0°	73,5°	73,0°	73,0°	73,0°
Vaakaputken pituus (mm)	530	545	560	575	590
Emäputken pituus (mm)	130	145	167	187	205
Emäputken kulma	71,5°	72,5°	72,5°	72,5°	72,5°
Haarukan offset (mm)	50	50	50	50	50
Akseliväli (mm)	994	995	1008	1023	1037,9
Takahaarukan alaputken pituus (mm)	420	420	420	420	420
Keskiön pudotus (mm)	80	80	75	75	75
Stack-mitta (mm)	542	560	576	595	612,4
Reach-mitta (mm)	374	379	384	393	402,6
Standover-mitta (mm)	716	746	779	799	824
Ohjaustangon leveys (mm)	400	420	420	440	440
Ohjainkannattimen pituus (mm)	90	100	110	110	120
Rengaskoko	700C	700C	700C	700C	700C

Kaikki ilmoitettut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.