

DEFY ADVANCED E+ ELITE 0

GIANT



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
SENSOR	Mode support switch from SRAM bonus button
PRIKAZ	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATERIJA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
OKVIR	
VELIČINE	S, M, ML, L, XL
BOJE	Midnight Moon
OKVIR	Advanced-grade composite, 12x145 thru-axle
VILICA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
AMORTIZER	-
KOMPONENTE	
VOLAN	Giant Contact SLR D-Fuse 31.8 carbon
LULA VOLANA	Contact SLR Aerolight 31.8 carbon
CIJEV SJEDALA	Giant D-Fuse SLR, Composite, -5/+15mm offset
SJEDALO	Giant Fleet SL
POGON	
RUČICE MJENJAČA	Sram RED AXS
PREDNJI MJENJAČ	Sram RED AXS
STRAŽNJI MJENJAČ	Sram RED AXS
KOČNICE	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
RUČICE KOČNICA	Sram RED AXS HRD
KAZETA	SRAM RED XG-1290 10x33T 12-speed
LANAC	Sram RED 12-speed
POGON	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
OSOVINA POGONA (BB)	Giant E+ System BBSS

KOTAČI	
OBRUČI	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
GUME	Cadex Race GC, tubeless, 700x30, folding
DODACI	Fender adapter
DODACI	
SVJETLA	Seatpost clamp integrated tail light

GEOMETRIJA

OKVIR	S	M	ML	L	XL
Dužina cijevi sjedala (mm)	445	480	515	535	565
Kut cijevi sjedala	74,0°	73,5°	73,0°	73,0°	73,0°
Dužina gornje cijevi (mm)	530	545	560	575	590
Dužina prednje cijevi (mm)	130	145	167	187	205
Kut vilice	71,5°	72,5°	72,5°	72,5°	72,5°
Zakrivljenost vilice (offset) (mm)	50	50	50	50	50
Staza (mm)	56,1	58,6	58,6	58,6	58,6
Međuosovinski razmak kotača (mm)	994	995	1008	1023	1037,9
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	420	420	420	420	420
Položaj osovine pogona (mm)	80	80	75	75	75
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	542	560	576	595	612,4
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	374	379	384	393	402,6
Prekoračna visina (mm)	716	746	779	799	824
Širina volana (mm)	400	420	420	440	440
Dužina lule volana (mm)	90	100	110	110	120
Veličina kotača	700C	700C	700C	700C	700C

Sve navedene specifikacije podložne su promjeni bez prethodne najave.