

DEFY ADVANCED E+ ELITE 0

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY

MOTORE	SyncDriveMove Plus Hub drive 75Nm max
COMANDO	Mode support switch from SRAM bonus button
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERIA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CARICATORE	Giant EnergyPak smart charger 4A
CONNETTIVITÀ	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile

TELAIO

TAGLIE	S, M, ML, L, XL
COLORAZIONI	Mariana Blue
TELAIO	Advanced-grade composite, 12x145 thru-axle
FORCELLA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc

AMMORTIZZATORE

	-
--	---

COMPONENTISTICA

MANUBRIO	Giant Contact SLR D-Fuse 31.8 carbon
ATTACCO MANUBRIO	Contact SLR Aerolight 31.8 carbon
REGGISSELLA	Giant D-Fuse SLR, Composite, -5/+15mm offset
SELLA	Giant Fleet SL

SISTEMA DI TRASMISSIONE

CAMBIO	Sram RED AXS
DERAGLIATORE ANTERIORE	Sram RED AXS
DERAGLIATORE POSTERIORE	Sram RED AXS
FRENI	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
COMANDI FRENO	Sram RED AXS HRD
PACCO PIGNONI	SRAM RED XG-1290 10x33T 12-speed
CATENA	Sram RED 12-speed
GUARNITURA	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
MOVIMENTO CENTRALE	Giant E+ System BBSS

RUOTE

CERCHI	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
COPERTONI	Cadex Race GC, tubeless, 700x30, folding
EXTRA	Fender adapter

ACCESSORI

ILLUMINAZIONE	Seatpost clamp integrated tail light
----------------------	--------------------------------------

Prezzo: 10.499,00 €

GEOMETRIA

TELAIO	S	M	ML	L	XL
Lunghezza Tubo Sella (mm)	445	480	515	535	565
Angolo Tubo Sella	74,0°	73,5°	73,0°	73,0°	73,0°
Lunghezza Tubo Orizzontale (mm)	530	545	560	575	590
Lunghezza Tubo Sterzo (mm)	130	145	167	187	205
Angolo Sterzo	71,5°	72,5°	72,5°	72,5°	72,5°
Rake Forcella (mm)	50	50	50	50	50
Avancorsa (mm)	56,1	58,6	58,6	58,6	58,6
Interasse (mm)	994	995	1008	1023	1037,9
Lunghezza Carro Posteriore (mm)	420	420	420	420	420
Drop Movimento Centrale (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Altezza stand over (mm)	716	746	779	799	824
Larghezza Manubrio c/c (mm)	400	420	420	440	440
Lunghezza Attacco Manubrio (mm)	90	100	110	110	120
Dimensione Ruote	700C	700C	700C	700C	700C

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.