

# DEFY ADVANCED E+ ELITE 0

**GIANT**



## SPECIFICATIES

### HYBRID CYCLING TECHNOLOGY

<b>MOTOR</b>	SyncDriveMove Plus Hub drive 75Nm max
<b>BEDIENINGSUNIT</b>	Mode support switch from SRAM bonus button
<b>DISPLAY</b>	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
<b>ACCU</b>	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
<b>LADER</b>	Giant EnergyPak smart charger 4A
<b>CONNECTIVITY</b>	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile

### FRAME

<b>MATEN</b>	S, M, ML, L, XL
<b>KLEUREN</b>	Midnight Moon
<b>FRAME</b>	Advanced-grade composite, 12x145 thru-axle
<b>VOORVORK</b>	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
<b>DEMPER</b>	-

### ONDERDELEN

<b>STUUR</b>	Giant Contact SLR D-Fuse 31.8 carbon
<b>STUURPEN</b>	Contact SLR Aerolight 31.8 carbon
<b>ZADELPEN</b>	Giant D-Fuse SLR, Composite, -5/+15mm offset
<b>ZADEL</b>	Giant Fleet SL

### AFMONTAGE

<b>SHIFTERS</b>	Sram RED AXS
<b>VOORDERAILLEUR</b>	Sram RED AXS
<b>ACHTERDERAILLEUR</b>	Sram RED AXS
<b>REMMEN</b>	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
<b>REMHENDELS</b>	Sram RED AXS HRD
<b>CASSETTE</b>	SRAM RED XG-1290 10x33T 12-speed
<b>AANDRIJVING</b>	Sram RED 12-speed
<b>CRANKSET</b>	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
<b>BOTTOM BRACKET</b>	Giant E+ System BBSS

### WIELSET

<b>VELGEN</b>	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
<b>BANDEN</b>	Cadex Race GC, tubeless, 700x30, folding
<b>EXTRA'S</b>	Fender adapter

### ACCESSOIRES

<b>VERLICHTING</b>	Seatpost clamp integrated tail light
--------------------	--------------------------------------

**Adviesprijs: € 10.499,00**

## GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	445	480	515	535	565
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	530	545	560	575	590
Balhoofdbuis Lengte (mm)	130	145	167	187	205
Balhoofdbuis Hoek	71,5°	72,5°	72,5°	72,5°	72,5°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	56,1	58,6	58,6	58,6	58,6
Wielbasis (mm)	994	995	1008	1023	1037,9
Liggende achtervork lengte (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Stand Over Height (mm)	716	746	779	799	824
Stuur breedte (mm)	400	420	420	440	440
Stuurpen Lengte (mm)	90	100	110	110	120
Wielmaat	700C	700C	700C	700C	700C

*Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.*