

DEFY ADVANCED E+ ELITE 0

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY

MOTOR	SyncDrive Move Plus Hub drive 75Nm max
BEDIENINGSUNIT	Mode support switch from SRAM bonus button
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
ACCU	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile

FRAME

MATEN	S, M, ML, L, XL
KLEUREN	Midnight Moon
FRAME	Advanced-grade composite, 12x145 thru-axle
VOORVORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
DEMPER	-

ONDERDELEN

STUUR	Giant Contact SLR D-Fuse 31.8 carbon
STUURPEN	Contact SLR Aerolight 31.8 carbon
ZADELPEN	Giant D-Fuse SLR, Composite, -5/+15mm offset
ZADEL	Giant Fleet SL

AFMONTAGE

SHIFTERS	Sram RED AXS
VOORDERAILLEUR	Sram RED AXS
ACHTERDERAILLEUR	Sram RED AXS
REMMEN	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
REMHENDELS	Sram RED AXS HRD
CASSETTE	SRAM RED XG-1290 10x33T 12-speed
AANDRIJVING	Sram RED 12-speed
CRANKSET	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
BOTTOM BRACKET	Giant E+ System BBSS

WIELSET

VELGEN	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
BANDEN	Cadex Race GC, tubeless, 700x30, folding
EXTRA'S	Fender adapter

ACCESSOIRES

VERLICHTING	Seatpost clamp integrated tail light
--------------------	--------------------------------------

Adviesprijs: € 10.499,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis lengte (mm)	445	480	515	535	565
Zitbuis hoek	74,0°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	530	545	560	575	590
Balhoofdbuis Lengte (mm)	130	145	167	187	205
Balhoofdbuis Hoek	71,5°	72,5°	72,5°	72,5°	72,5°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	56,1	58,6	58,6	58,6	58,6
Wielbasis (mm)	994	995	1008	1023	1037,9
Liggende achtervork lengte (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Stand Over Height (mm)	716	746	779	799	824
Stuur breedte (mm)	400	420	420	440	440
Stuurpen Lengte (mm)	90	100	110	110	120
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.